

345 W Chestnut Ave Monrovia, CA 91016-3317 626-357-8743 626-357-7284 FAX

https://www.argonmasking.com



## **Argon PC500 Polyimide Tape**

**Product description**: 1.0 mil polyimide film with a 1.5 mil pressure sensitive silicone adhesive withstands temperatures up to 500°F (260°C).

## **Application advantages:**

- Offers optimal performance in electrical and thermal insulation.
- Highly resistant to heat and chemicals
- Thin and highly conformable.
- Puncture and tear resistant at high temperatures.
- One year shelf life.

Physical Properties**:	Typical Values	Test Method
Total thickness	2.5 mil	ASTM D3652
Backing thickness	1.0 mil	<b>ASTM D3652</b>
Adhesive thickness	1.5 mil	<b>ASTM D3652</b>
Backing	Polyimide Film	
Adhesive type	Silicone	
Adhesion to steel	23 oz/in	ASTM D3330
Tensile Strength	28 lb/in	<b>ASTM D3759</b>
Elongation	63%	<b>ASTM D3759</b>
Dielectric Strength	6,200 volts	ASTM D149
Roll Length	36 yards	
Color	Amber	

<sup>\*\*</sup>This information is offered as a guide to aid in proper selection. The user must determine the suitability of the product for the intended use. Because of varied applications and performance conditions, our products are warranted against manufacturing defects only.