

## Data Sheet

### Models 1785B, 1786B, 1787B & 1788

#### Programmable DC Power Supplies

Models 1785B, 1786B, 1787B & 1788 are Programmable DC Power Supplies that offer new levels of "ease of use" and programmable functionality. Direct key in entry makes voltage and current selection fast, accurate and easy. In case calibration allows for simple, cost savings, uninterrupted operation.

- Sixteen user programmable preset outputs
- Controllable Output On/Off Switch
- 10mV/10mA setable resolution
- Closed case calibration
- Low ripple and noise
- Excellent temperature stability
- Serial interface cable and software included



Model 1788

Specifications		models			
		1785B	1786B	1787B	1788
Parameter					
Output Ratings, (0 °C - 40 °C)					
Voltage	0 ~18V	0 ~32V	0 ~72V	0 ~32V	
Current	0 ~5A	0 ~3A	0~1.5V	0~6A	
Load Regulation, ±(% of output + offset)					
Voltage	<0.01% + 3mV, Model 1788 = <0.02% + 5mV				
Current	<0.1% + 2mA				
Line Regulation, ±(% of output + offset)					
Voltage	<0.1% + 3mV				
Current	<0.1% + 2mA				
Ripple, (20Hz ~20MHz)					
Voltage	≤ 1mVrms/3mVp-p				
Current	5mA rms				

### B&K Precision Corporation

22820 Savi Ranch Parkway, Yorba Linda, CA 92887  
Tel: 714-921-9095, Fax: 714-921-6422  
www.bkprecision.com

Specifications subject to change without notice