CU-3286 & CU-3286-MB CUR-3286 & CUR-3286-MB CUR-3286-C & CUR-3286-CMB PART PART REV. UTILIBOX (STYLE A) 9-2-10 NAME No. DATE MATERIAL: BODY AND STANDARD COVERS SIX (6) #4-40 x 0.500" LG. SCREWS ABS THERMOPLASTIC (FLAMMABILITY RATING UL94-5VA) SUPPLIED FOR ASSEMBLING COVER RECESSED COVERS (CUR-) TO BODY ABS THERMOPLASTIC (FLAMMABILITY RATING UL94-5VA) CLEAR COVERS (-C) MOUNTING BOSSES USE EITHER M2.5 ABS THERMOPLASTIC (FLAMMABILITY RATING UL94V-2) METRIC OR #4 STD. SHEET METAL FINISH SCREWS × 0.250" LG. BODY AND STANDARD COVERS ARE BLACK TEXTURED (NOT SUPPLIED) RECESSED (CUR-) AND CLEAR COVERS (-C) ARE SMOOTH FINISH —— 10.151 — **-** 0.125 **◄** 4.583 − – 4,585 — 0.125 -4.656 TEXTURED FLUSH OR 6.151 0.030 RECESSED SMOOTH 5.170 —— 8,656 – #4-40 THREADED INSERT —— 11.400 — (6) PLACES 4.585 — **◄** 4,585 -**-**─ 3,000 — 0 0 0 -0.250 DIA. BOSS (8) PLACES 4.000 - **—** 4.500 6.151 6.000 5.170 └0.086 × 0.250 DEEP (8) PLACES (3 PLACES) 0 **→** 0.750 0.250 DIA. (4) HOLES (TO FIT A #6 SCREW) - 3,875 ----- 3,875 *-*-—— 10.750 — 10.000 — NOTE: ALL DIMENSIONS HAVE ±0.010 TOLERANCE UNLESS OTHERWISE 1-1/2° DRAFT 0.105 SPECIFIED. ALL DUTSIDE WALL SURFACES 1/2° DRAFT ALL INSIDE SURFACES - 0.250 (TYP) - 0.125 PART No. TEXTURED FLUSH COVER LESS RECESS AND BODY WITHOUT MOUNTING FLANGE CU-3286 TEXTURED FLUSH COVER LESS RECESS AND BODY WITH MOUNTING FLANGE. CU-3286-MB CUR-3286 COVER WITH SMOOTH 0.030 RECESS AND BODY WITHOUT MOUNTING FLANGE. CUR-3286-MB COVER WITH SMOOTH 0.030 RECESS AND BODY WITH MOUNTING FLANGE