

HYTOOL[™] Hand-Operated Crimper, Installs #14 - 4/0 AWG, Permanent BG (5/8) and D3 grooves

By Burndy Catalog # MD6



Crimper, Installs #14-4/0 AWG, BG & D3 Grooves.

Features

- Ergonomically designed, one-piece, composite polymer handles
- Comfort grip handles
- Time-proven steel jaw designs
- No tool adjustment required
- 99,000 crimp/cycle life
- Positive lock, spring loaded die retainer buttons
- PTFE impregnated steel/bronze bushings and stainless steel pins
- · Electroless nickel plated jaws and jaw links

General

uminum, ACSR, perweld, Alumoweld, , Compressed and
Conductors
X Die
ated Crimper
003
0033

Dimensions

Dimensions	25.38 in x 7.04 in x 2.00 in
Height	2 in
Length	25.38 in
Weight	6.25 lb
Width	7.04 in

Conductor Related

Crimping Ranges

Copper: 10 sol. - 500 Kcmil; Copper Flex: #8 to 350 kcmil

Certifications And Compliance

Standards - RoHS Compliance EX Status

Logistics

Minimum Pack Quantity1Package ContentsTool only

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section N - Tooling Customer Notices - Prop 65 Notice Installation Manuals - BUR_464750_MD6_MD66_MD637_MD638 Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_MD6_Lineart Sales Drawings - 2240



©2024 Hubbell Incorporated. All rights reserved BRDY-MD6-SPEC-EN | REV 6/2024