



HYTOOL™ Series, Hand-Operated Crimper, Polymer Handles, #14 - 4/0 AWG, Permanent O and D3 grooves

By Burndy
Catalog # MD78

HYTOOL™ #14-4/0, Perm O/D3, Composite

Features

- Ergonomically designed, one-piece, composite polymer handles
- Comfort grip handles
- Time-proven steel jaw designs
- No tool adjustment required
- 99,000 crimp/cycle life
- Positive lock, spring loaded die retainer buttons
- PTFE impregnated steel/bronze bushings and stainless steel pins
- Electroless nickel plated jaws and jaw links

Application

Crimping

Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Standards - RoHS Compliance Status	EX

Conductor

Crimping Ranges	• Taps: Copper: #10 sol. to 2/0 str., Aluminum & ACSR: #14 sol. to 4/0 ACSR • Stirrups: #6 to 4/0 ACSR • Overhead Full Tension Deadends, Full Tension Splices and Terminals: #10 str. to 4/0 ACSR • Installs Splices, Taps or Terminations: #8 to 500 kcmil Copper Stranded, #8
-----------------	---



to 350 kcmil Copper Flex,
#8 to 350 kcmil Aluminum

Dimensions

Length	25 in
Width	4.5 in
Weight	7 lb.
Height	2 in
Dimensions	25 in x 4.5 in x 2 in

Force Related

Crimp Force Capacity	4.5 ton
----------------------	---------

General

Sub Brand	HYTOOL
Series	HYTOOL™ Series
Trade Name	POSI-PRESS™ HYTOOL™
Application - For Use On	Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed and Compact Conductors
UPC 12 Digit	781810010907
UPC 14 Digit GTIN	00781810010907
Tool Type	Hand Operated Crimper
UPC	781810010907
Die Type	W and X Die

Logistics

Package Contents	Tool only
Minimum Pack Quantity	1

Product Assets

[Catalog \[English\]](#)