


## Stacking Banana Plug Test Lead

4mm Stacking, Retractable Sleeve, Straight, Banana Plug to Stacking, Retractable...

### Description

Added safety and protection when standard banana jack connections are encountered. With Silicone jacketed wire, 0.75 mm<sup>2</sup> (18 AWG). Clear covering sleeve retracts as you plug into the jack. Banana plug includes a Grey plastic insulation tip for added protection.

- Materials: Body: Polyamide; Contact: Brass, Nickel Plt.
- Banana Contact: BeCu, Nickel Plt.
- Meets IEC 61010-031 safety specifications
- Available in 6 standard lengths
- Available in 6 colors



*Technical data subject to change.*

© Cal Test Electronics 2018.

[caltestelectronics.com](http://caltestelectronics.com)

All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25°C ± 5°C.

### **Specifications**

<b>IEC Rating</b>	600 V CAT II
<b>Current Max</b>	12 A
<b>Resistance Max</b>	10 milliohms
<b>Jacket Material</b>	Silicone
<b>Conductor Area</b>	0.75 mm <sup>2</sup>
<b>Wire Gauge</b>	18 AWG
<b>Stranding (# x dia.)</b>	195 x 0.07 mm
<b>Jacket OD</b>	3.7 mm (0.146")
<b>Temperature (degrees)</b>	-20 to +80C
<b>RoHS (2011/65/EU)</b>	Compliant

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: [caltestelectronics.com](http://caltestelectronics.com)