

# CT3096

## MiniFlex Clip Lead to 4mm Jack, Pair


Connect to your MiniFlex clip to a 4mm Sheathed DMM...

### Description

Connect to your MiniFlex clip to a 4mm Sheathed DMM lead.

Very versatile test lead.

- Material: Polyamide (Nylon) w/Stainless Steel Contacts
- Highly flexible Silicone jacketed wire
- Available in black and red pair



*Technical data subject to change.*

© Cal Test Electronics 2018.

[caltestelectronics.com](http://caltestelectronics.com)

# Datasheet

All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25°C ± 5°C.

### Specifications

<b>IEC Rating</b>	33 Vac / 70 Vdc
<b>Current Max</b>	1 A
<b>Jacket Material</b>	Silicone
<b>Conductor Area, square millimeters</b>	0.40
<b>Length</b>	10 cm
<b>Wire Gauge, AWG</b>	21
<b>Stranding, # x mm</b>	100 x 0.07
<b>OD, mm (in)</b>	2.1mm (0.083")
<b>Temperature (degrees)</b>	-20 to +80 degC
<b>RoHS (2011/65/EU)</b>	Compliant

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: [caltestelectronics.com](http://caltestelectronics.com)

*Technical data subject to change.*

© Cal Test Electronics 2018.

[caltestelectronics.com](http://caltestelectronics.com)

