

# Geared Wrenches

Cementex Geared Wrenches are double insulated with a continuous outer layer of orange insulation to provide a smooth transition between the dual-layer and single-layer portions of each tool. These wrenches provide the secure hold and size benefits of the Cementex box end wrenches with the added feature of a ratcheting head. The precision ratcheting head is guaranteed to withstand your heavy work load while saving valuable time.



- Newly redesigned and perfected over time
- Slender head allows access to tight locations
- Reverse direction by flipping wrench over

*Wide range of sizes and length. Custom sizes available.*


SAE Options	
Part Number	Size
IGW-08	1/4"
IGW-10	5/16"
IGW-12	3/8"
IGW-14	7/16"
IGW-16	1/2"
IGW-18	9/16"
IGW-20	5/8"
IGW-22	11/16"
IGW-24	3/4"
IGW-26	13/16"
IGW-28	7/8"
IGW-30	15/16"
IGW-32	1"
IGW-34	1-1/16"
IGW-36	1-1/8"
IGW-40	1-1/4"

Metric Options	
Part Number	Size
IGW-06M	6mm
IGW-07M	7mm
IGW-08M	8mm
IGW-09M	9mm
IGW-10M	10mm
IGW-11M	11mm
IGW-12M	12mm
IGW-13M	13mm
IGW-14M	14mm
IGW-15M	15mm
IGW-16M	16mm
IGW-17M	17mm
IGW-18M	18mm
IGW-19M	19mm
IGW-20M	20mm
IGW-21M	21mm
IGW-22M	22mm
IGW-24M	24mm
IGW-25M	25mm
IGW-27M	27mm
IGW-30M	30mm
IGW-32M	32mm

Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V

