

## Liquid Flux No-Clean in 30ml (1.0oz) Squeeze Bottle w/tip

### Product Highlights

A liquid flux that is non-flammable  
No-Clean  
Water-Based, leaves no residues  
VOC Free, Halide Free, Rosin Free  
Ideal for all rework, solder, and de-solder applications  
Excellent wetting  
Easily cleaned with isopropyl alcohol (IPA)  
Can be used with Leaded and Lead-Free applications  
**RoHS 3 and REACH compliant**



### Specifications

|                      |  |
|----------------------|--|
| Flux Type:           | No-Clean Liquid Flux (for Leaded and Lead-Free applications) |
| Flux Classification: | ORL0   |
| VOC Content:         | VOC Free   |
| Specific Gravity:    | 1.01   |
| Packaging:           | 30ml Squeeze Bottle  |
| Shelf Life:          | Refrigerated >24 months, Unrefrigerated >24 months           |

### Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

### Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

### Cleaning

This is a no-clean liquid flux, post-use cleaning is not required.

Conforms to the following Industry Standards:

|  |     |
|--|-----|
| J-STD-004B, Amendment 1 (Solder Fluxes): | Yes |
| RoHS 3 Directive 2015/863/EU:            | Yes |