# **Safety Data Sheet**

115-3302

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA Revision Date: May 30, 2024

Phone: 978-373-1600 | Website: www.circuitmedic.com

CircuitMedic disclaims all liability associated with the use of this information.

**Print** 

#### Section 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Circuit Bond - Hardener	
Product Number:	115-3302	
UFI Number:	P321-AAMU-S30E-T3VS	
Recommended use:	This general-purpose adhesive is packaged in a two-part plastic package. The components are mixed just before use. There are no identified uses advised against.	
	The components include:	
	115-3302 Circuit Bond - Resin	
	http://www.circuitmedic.com/msds/msds_circuit_bond_resin.html	
	115-3302 Circuit Bond - Hardener	
	http://www.circuitmedic.com/msds/msds_circuit_bond_hardener.html	
Supplier:	CircuitMedic 22 Parkridge Road, Haverhill, MA 01835 USA PHONE: 978-373-1600, FAX: 978-372-5700	
Emergency	For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident	
Response:	Call CHEMTREC Day or Night	
	Within USA and Canada: 1-800-424-9300 CCN4877	
	Outside USA and Canada: +1 703-527-3887 (collect calls accepted)	

#### Safety Data Sheet No. 115-3302

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA

Page 1 of 11

Revision Date: May 30, 2024

#### **Section 2. HAZARD IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830

### **Hazard pictograms:**





Signal Words:	DANGER
GHS Class:	Serious Eye Damage, category 1, Skin corrosion, category 1, Skin Sensitization, category 1 Specific Target Organ Toxicity - STOT, Single Exposure SE. Category 3 (Respiratory tract irritation)
Hazard Statements:	H318 - Causes serious eye damage. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H335 - May cause respiratory irritation.
Precautionary Statements:	P260 - Do not breathe dust/fume/gas/mist/vapors/spray. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Do not allow contaminated clothing out of the workplace. P280 - Wear protective gloves/protective clothing/eye and face protection. P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P303+P361+P353 - IF ON SKIN (or hair): Immediately remove all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present, and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P333+P313 - If skin irritation or rash occurs, get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place and keep the container closed. P405 - Store locked up. P501 - Dispose of contents/container in accordance with Local, State, Federal, and Provincial regulations.
Hazards not otherwise classified:	

#### Safety Data Sheet No. 115-3302

Page 2 of 11

Revision Date: May 30, 2024

# **Section 3. COMPOSITION, INFORMATION OR INGREDIENTS**

Chemical/Ingredient Name	CAS Number	Ingredient Percent	EC Number	Comments
Diethylenetriamine	111-40-0	10 - 30	203-865-4	-
Epoxy polyamine adduct	Proprietary	60 - 100	-	-

# **Section 4. FIRST AID MEASURES**

4.1 Description of first aid measures		
Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.	
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.	
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.	
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.	
4.2. Most im	portant symptoms and effects, both acute and delayed	
None		
4.3 Indication of any immediate medical attention and special treatment needed		
No additional information.		

#### Safety Data Sheet No. 115-3302

Page 3 of 11

Revision Date: May 30, 2024

# **Section 5. FIRE-FIGHTING MEASURES**

5.1 Extinguishing media		
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.	
Unsuitable Media:	None.	
5.2 Special hazards ari	ising from the substance or mixture	
Hazardous Combustion Byproducts:	Oxides of carbon, aldehydes, amines, aniline, acids and other organic substances may be formed during combustion. The chemical nature and quantity of decomposition by-products will vary widely depending on the conditions of combustion.	
Unusual Fire Hazards:	Sealed containers at elevated temperatures may rupture explosively and spread fire due to polymerization.	
5.3 Advice for firefight	rers	
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.	
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.	
NFPA Health:	3	
NFPA Fire:	1	
NFPA Reactivity:	1	

# Safety Data Sheet No. 115-3302

Page 4 of 11

Revision Date: May 30, 2024

### **Section 6. ACCIDENTAL RELEASE MEASURES**

6.1 Personal pre	ecautions, protective equipment and emergency procedures	
Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in Section 8.	
6.2 Environmen	tal precautions	
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.	
6.3 Methods and	d material for containment and cleaning up	
Methods for Containment:	For small spills, activate available exhaust ventilation equipment in the immediate spill area. Wipe up or absorb spilled material with paper towels or other absorbent material. For large spills, dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters.	
Methods for Cleanup:	For small spills, wash area with soapy water to remove residue. Collect absorbed material and water rinses in appropriate containers. Dispose of in accordance with Federal, State and local regulations. For large spills, recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitible vapors, have been removed thoroughly wet vacuum the area. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Do not flush to sewer.	
Other Spill Precautions:	Spill response operations must be conducted in accordance with the provisions of OSHA 29 CFR 1910.120. Review the entire SDS before proceeding with spill response.	
6.4 Reference to	o other sections	
Use proper persor	nal protective equipment as listed in Section 8.	

### **Section 7. HANDLING AND STORAGE**

7.1 Precauti	ons for safe handling	
Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Avoid contact with eyes, skin, or clothing. Avoid prolonged or repeated contact with skin. Keep container tightly closed when not in use.	
Special Handling:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.	
Hygiene Practices:	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using restroom facilities. Promptly remove contaminated clothing and launder thoroughly before reuse.	
7.2 Conditio	ns for safe storage, including any incompatibilities	
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep containe tightly closed when not in use. Do not reuse empty containers. Keep out of the reach of children.	
7.3. Specific	end use(s)	
No additional information.		

### Safety Data Sheet No. 115-3302

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA

Revision Date: May 30, 2024

Page 5 of 11

# **Section 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**

8.1 Control p	arameters	
Exposure Gui	delines	
Diethylenetriamine:		
ACGIH:	Skin:Skin	
8.2 Exposure	controls	
Appropriate 6	engineering controls	
Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.	
Individual pro	otection measures	
Eye Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.	
Skin Protection:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.	
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant the use of respirators.	
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.	
Hygiene Practices:	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using restroom facilities. Promptly remove contaminated clothing and launder thoroughly before reuse.	

### Safety Data Sheet No. 115-3302

Page 6 of 11 Revision Date: May 30, 2024

# **Section 9. PHYSICAL AND CHEMICAL PROPERTIES**

9.1 Information on basic physical and chemical properties		
Physical State:	Liquid.	
Color:	Clear amber	
Odor:	Amine like odor	
рН:	Not determined.	
Melting Temperature:	Not determined.	
Boiling Temperature:	Greater than 374 °F	
Flash Point:	Greater than 212 °F	
Flash Point Method:	Not determined.	
Ignition Temperature:	Not determined.	
Lower Flammable Limit:	Not determined.	
Vapor Pressure:	Not determined.	
Vapor Density:	Not determined.	
Solubility:	Not determined.	
Specific Gravity:	(Ref: water = 1).	
Evaporation Rate:	Not determined.	
VOC Content:	Not determined.	
Viscosity:	Not determined.	
Odor Threshold:	Not determined.	
9.2 Other information		
None available.		

### Safety Data Sheet No. 115-3302

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA

Page 7 of 11 Revision Date: May 30, 2024

# **Section 10. STABILITY AND REACTIVITY**

10.1 Reactivity			
Reactivity:	Stable under normal handling and storage conditions.		
10.2 Chemical Stabili	10.2 Chemical Stability		
Chemical Stability:	Stable under normal temperatures and pressures.		
10.3 Possibility of ha	zardous reactions		
Hazardous Polymerization:	It will not vigorously polymerize, decompose, condense or not become self-reactive under conditions of shocks, pressure, or temperature. Uncontrolled mixing with resins may cause hazardous polymerization.		
10.4 Conditions To Av	void		
Conditions To Avoid:	Contact with acidic, basic, or oxidizing materials. Exposure to open flame or uncontrolled heat, uncontrolled mixing or exposure to incompatible substances. Avoid storage in open containers.		
10.5 Incompatible Materials			
Incompatible Materials:	Acidic, basic or oxidizing materials.		
10.6 Hazardous decomposition products			
None known.			

# **Section 11. TOXICOLOGICAL INFORMATION**

11.1 Information	on on toxicological effects	
Diethylenetrian	nine:	
Skin Toxicity:	Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 1090 mg/kg [Details of toxic effects not reported other than lethal dose value](RTECS)	
Ingestion Toxicity:	Oral - Rat LD50 - Lethal dose, 50 percent kill: 1080 mg/kg [Behavioral - Convulsions or effect on seizure threshold] (RTECS)	
Inhalation Toxicity:	Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: >0.07 - <0.3 mg/l (Supplier SDS)	
Epoxy polyamine adduct:		
Ingestion Toxicity:	Oral - Rat LD50 - Lethal dose, 50 percent kill: 200 - 500 mg/kg (Manufacturer Studies)	

Safety Data Sheet No. 115-3302

Page 8 of 11 Revision Date: May 30, 2024

#### Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity			
Ecotoxicity:	No ecotoxicity data was found for the product.		
12.2 Persistence and degradability			
nvironmental Fate: No environmental information found for this product.			
12.3 Bioaccumulative potential			
No data available.			
12.4 Mobility in soil			
No data available.			

# **Section 13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

## Waste Disposal:

Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws. Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

Do not reuse, heat, burn, pressurize, cut, weld, braze, solder, drill, grind, expose to sparks, flame, or ignition sources of empty containers without proper commercial cleaning or reconditioning.

#### Safety Data Sheet No. 115-3302

Page 9 of 11

Revision Date: May 30, 2024

# **Section 14. TRANSPORT INFORMATION**

14.1 UN Number:	UN2735
14.2 UN proper shipping name:	Amines, liquid, corrosive, n.o.s. (Diethylenetriamine)
14.3. Transport hazard class(es):	8
14.4 Packing group:	III
14.5 Environmental hazards	Environmentally hazardous substance, liquid, n.o.s.
14.6 Special precautions for user	None.
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
DOT Shipping Name:	Amines, liquid, corrosive, n.o.s. (Diethylenetriamine)
DOT UN Number:	UN2735
DOT Hazard Class	8
DOT Packing Group:	III
IMDG Shipping Name:	Amines, liquid, corrosive, n.o.s. (Diethylenetriamine)
IMDG UN Number:	UN2735
IMDG Hazard Class:	8
IMDG Packing Group:	III
IATA Shipping Name:	Amines, liquid, corrosive, n.o.s. (Diethylenetriamine)
IATA UN Number:	UN2735
IATA Hazard Class:	III
IATA Subrisk:	8
Notes from Section 14:	The data provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment. This classification applies only to transportation classification and not the packaging, labeling, or marking requirements. The shipper is responsible for complying with all applicable laws and regulations, including proper transportation classification, packaging, and labeling.

### Safety Data Sheet No. 115-3302

Revision Date: May 30, 2024

Page 10 of 11

#### Section 15. REGULATORY INFORMATION

15.1 Safety, hea	Ith and environmental regulations/legislation specific for the substance or mixture
EU legislation:	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).  COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
Regulatory - Ing	redient Based:
Diethylenetriami	ine:
Canada DSL:	Listed
TSCA Inventory Status:	Listed
EC Number:	203-865-4
15.2 Chemical sa	ofety assessment
Product does not o	ontain controlled chemicals listed in Table I and Table II of the 1988 UN Convention Against Illicit Traffic in

# **Section 16. OTHER INFORMATION**

Narcotic Drugs and Psychotropic Substances .

HMIS:	Health	3
	Flammability	1
	Reactivity	1
	PPE	X
NFPA	3 1	

To the best of our knowledge, the information contained herein is accurate. However, neither Circuit Technology Center, Inc., nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. The final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

# **Safety Data Sheet**

115-3302

Page 11 of 11

CircuitMedic, 22 Parkridge Road, Haverhill, MA 01835 USA Phone: 978-373-1600 | Website: www.circuitmedic.com

CircuitMedic disclaims all liability associated with the use of this information.

Revision Date: May 30, 2024