# Statfree<sup>®</sup> Dissipative Burnishing Restorer **Application Instructions**





Figure 1. Statfree® Dissipative Burnishing Restorer

## Description

Statfree® Dissipative Burnishing Restorer is a ready-to-use formulation that enhances gloss well beyond burnishing alone. It may be used with Statguard<sup>®</sup> Dissipative Floor Finish or with ESD floor tiles to clean and prepare the ESD flooring for burnishing in one simple step, keeping the wet look on floors without the need for refinishing. The surface resistance <  $1 \times 10^9$  ohms meets the ANSI/ESD S20.20 minimum requirements for an ESD protective floor and will not inhibit the ESD properties of Statguard® Dissipative Floor Finish or ESD tile that it is used with.

### Application

Heavy to moderate traffic floors should be treated once a week. Light traffic floors should be treated 2 to 4 times per month or as needed.

#### **EQUIPMENT NEEDED:**

- Push broom
- 1000-2000 rpm buffing machine with a white or beige pad
- Statfree<sup>®</sup> Burnishing Restorer
- Dry mop the coated area to remove loose dirt from 1. coated floor.
- Use a clean untreated string mop to apply a thin 2 coat of restorer onto floor. Allow it to dry 20 to 40 minutes.
- 3. Burnish the coated area with a 1000 to 2000 RPM burnishing machine and a clean beige burnishing pad.
- Dry mop the entire burnished area again. 4.

### **Physical Properties**

% Solids	6 - 10%
рН	6.0 - 7.0
Color	Light Blue
Coverage	2,000 sq.ft./gallon
Storage Temperature	35°F - 95°F
Freeze/Thaw Stability	Passes three cycles
Drying Time	20 - 40 min. @ 55% RH
Surface Resistance (Installed/Applied Material)	< 1 x 10 <sup>9</sup> ohms per ANSI/ESD STM7.1 and ESD TR53

#### Storage

Statfree® Dissipative Burnishing Restorer does not have a set life span. The chemicals are not known to degrade over time when stored at the proper temperature conditions as stated in the Safety Data Sheet. We also recommend that the product be stored in its original container and be sealed when not in use.

**RoHS 3, REACH, and Conflict Minerals Statement** See the Desco Industries RoHS 3, REACH, and Conflict Minerals Statement: DescoIndustries.com/ROHS3.aspx

**Desco Industries Limited Warranty** See the Desco Industries Limited Warranty: DescoIndustries.com/Warranty.aspx

Statfree<sup>®</sup> Dissipative Burnishing Restorer is available from these Desco Industries brands:

# DESCO

for service and support in North America 2.5 Gallons 81061

#### **STATGUARD** FLOORING

for service and support in North America 2.5 Gallons 46011

# DESCO ASIA

for service and support in Asia 10 Liters 81061

DESCO INDUSTRIES INC - 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Website: Descolndustries.com