



### Specifications

Band Circumference	4.75 to 12.25 in. (121 to 311 mm)
Link Width	0.25 in. (6 mm)

Item	Description
<a href="#">09080</a>	Wristband Only
<a href="#">09081</a>	Wristband with 6' Coil Cord
<a href="#">09082</a>	Wristband with 12' Coil Cord

### Features and Components

- A. ABS cap with slotted opening for size adjustment
- B. 300 series stainless steel back plate
- C. 4 mm snap stud machined from 300 series stainless steel. Fits to 4 mm spring loaded socket. Coil cord disengages from snap with 1-5 lbs. of perpendicular force.
- D. Inside links constructed of 300 series stainless steel
- E. Link exterior is covered with a .002" polyphenylsulfone insulated cap. Provides greater than 5,000 volts RMS insulation per ASTM D149.
- F. Size is adjusted by sliding 1 to 6 links on each side of the buckle
- G. Underwriters Laboratories listing 90P1C

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1

All tolerances are ±10% unless otherwise specified

### ULTRA LIGHT METAL EXPANSION WRISTBAND



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEBSITE: [Desco.com](http://Desco.com)  
 PHONE (909) 627-8178  
 DESC0 EAST: ONE COLGATE WAY, CANTON, MA 02021-1407  
 PHONE (781) 821-8370

**DRAWING  
NUMBER**  
09080

**DATE**  
September  
2018