



Specifications:

- A. 36 inch cable length
- B. 41-1/2 inch overall length
- C. Cable is constructed from braided Stainless Steel.
- D. Spring loaded connector clamps

Installation Instructions:

1. Attach clamps on each end of the cable to good connection points on mobile equipment.
2. Ensure connection points on mobile equipment are clean of debris and grime build up by cleaning with an IPA wipe or similar to prevent a resistance barrier from allowing a good connection between the clamp and mobile equipment connection points.
3. The cable is designed to provide downward spring like flexibility to increase pressure for a secure connection. Attach one clamp on one side under mobile equipment, extend cable under mobile equipment allowing maximum connection to floor and attach the clamp on the other end of cable to the opposite side of mobile equipment.
4. The cable should have limited play so that the cable doesn't flop when mobile equipment is moved, and the cable's flexible properties provide a spring like effect to push downward onto the floor.

Dimensional tolerances are +/- 10% unless otherwise specified

Specifications and procedures subject to change without notice.



Made in the
United States of America

GROUNDING CABLE, MOBILE CART, STAINLESS STEEL

DESCO

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com
PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
PHONE (781) 821-83700

**DRAWING
NUMBER**

14001

DATE

April
2025