# PROBRANDS

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Dykem® Cross Check™ Torque Seal® - Blue

Other means of identification

Part Number 83318

**Recommended use** Inspection Paint **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway

Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSerious eye damage/eye irritationCategory 1Sensitization, skinCategory 1

Carcinogenicity Category 2

Specific target organ toxicity, repeated

exposure

Aspiration hazard

Josuie

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause an allergic

skin reaction. Causes serious eye damage. Suspected of causing cancer. Causes damage to

Category 1

Category 1 (central nervous system)

organs (central nervous system) through prolonged or repeated exposure.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face

protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair):

Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use

appropriate media to extinguish.

**Storage** Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: Dykem® Cross Check™ Torque Seal® - Blue 83318 Version #: 04 Revision date: 06-14-2021 Issue date: 12-30-2020

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Light Mineral Spirits		64742-88-7	30 - 40
Diacetone Alcohol		123-42-2	1 - 5
Methyl Ethyl Ketoxime		96-29-7	1 - 5
Ethylbenzene		100-41-4	0.1 - 1

## 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic

effects.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters of ignition and flash back. During fire, gases hazardous to health may be formed. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapor.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

## Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

# Conditions for safe storage. including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for A Components	ir Contaminants (29 CFR 1910. Type	1000) Value	
Diacetone Alcohol (CAS 123-42-2)	PEL	240 mg/m3	
		50 ppm	
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Diacetone Alcohol (CAS 123-42-2)	TWA	50 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
Diacetone Alcohol (CAS 123-42-2)	TWA	240 mg/m3	
		50 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
	TWA	435 mg/m3	
		100 ppm	

Material name: Dykem® Cross Check™ Torque Seal® - Blue

SDS US

# US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
Methyl Ethyl Ketoxime (CAS 96-29-7)	TWA	36 mg/m3	
		10 ppm	

#### **Biological limit values**

<b>ACGIH</b>	<b>Biological</b>	<b>Exposure</b>	Indices

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release,

exposure levels are not known, or any other circumstances where air-purifying respirators may not

provide adequate protection.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Liquid.
Color Blue.
Odor Mild.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

276.98 - 485.06 °F (136.1 - 251.7 °C)

Flash point 105.1 °F (40.6 °C)
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits
Flammability limit - lower 1.1 %

Flammability limit - lower (%)

Flammability limit - upper

7 %

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressureNot available.Vapor density> 1 (air = 1)Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

VOC 37.62%, 364 g/L

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

decomposition temperature. Avoid temperatures exceeding the flash point. Contact with

incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

Carbon oxides.

## 11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

**Eye contact** Causes serious eye damage.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

Components	Species	Test Results
Diacetone Alcohol (CAS 1	123-42-2)	
<u>Acute</u>		
Dermal		
LD50	Rat	> 1900 mg/kg, 24 Hours
Oral		
LD50	Rat	3000 mg/kg
Ethylbenzene (CAS 100-4	11-4)	
<u>Acute</u>		
Oral		
LD50	Rat	3500 mg/kg

Components Species Test Results

Light Mineral Spirits (CAS 64742-88-7)

Acute Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

Vapor

LC50 Rat > 4.5 mg/l, 4 Hours

> 0.1 mg/l, 8 Hours

Oral

LD50 Rat > 5000 mg/kg

Methyl Ethyl Ketoxime (CAS 96-29-7)

Acute Dermal

LD50 Rabbit > 1000 mg/kg, 24 Hours

Inhalation

Vapor

LC50 Rat > 4.8 mg/l, 4 Hours

Oral

LD50 Rat > 900 mg/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

**ACGIH Carcinogens** 

Ethylbenzene (CAS 100-41-4)

A3 Confirmed animal carcinogen with unknown relevance to

humans

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs (central nervous system) through prolonged or repeated exposure.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated

exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** 

Diacetone Alcohol (CAS 123-42-2)

Aquatic

Acute

LC50 Fish Bluegill (Lepomis macrochirus) 420 mg/l, 96 hours

Ethylbenzene (CAS 100-41-4)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours LC50 Fish Atlantic silverside (Menidia menidia) 4.4 - 5.7 mg/l, 96 hours

Methyl Ethyl Ketoxime (CAS 96-29-7)

Aquatic

Acute

LC50 Fish Fathead minnow (Pimephales promelas) 777 - 914 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Diacetone Alcohol -0.098Ethylbenzene 3.15

Mobility in soil Not established. Other adverse effects None known.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

D001: Waste Flammable material with a flash point <140 F Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

#### 14. Transport information

DOT

UN1263 **UN number UN** proper shipping name Paint

Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B1, B52, IB3, T2, TP1, TP29

Packaging exceptions 150 Packaging non bulk 173 Packaging bulk 242

IATA

UN1263 **UN number UN proper shipping name** Paint

Transport hazard class(es)

Class 3 Subsidiary risk

**Packing group** Ш **Environmental hazards** No. **ERG Code** 3L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Not applicable.

Cargo aircraft only Allowed with restrictions.

**IMDG** 

**UN** number UN1263 **PAINT UN proper shipping name** 

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group **Environmental hazards** 

Marine pollutant No. **EmS** F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

#### DOT



IATA; IMDG



## 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Ethylbenzene (CAS 100-41-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation Respiratory or skin sensitization

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
ETHYLBENZENE	100-41-4	0.1 - 1	

## Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

### **US state regulations**

#### US. New Jersey Worker and Community Right-to-Know Act

Diacetone Alcohol (CAS 123-42-2) Ethylbenzene (CAS 100-41-4)

#### **California Proposition 65**



WARNING: This product can expose you to chemicals including Ethylbenzene, which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethylbenzene (CAS 100-41-4)

### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

#### 16. Other information, including date of preparation or last revision

**Issue date** 12-30-2020

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision date 06-14-2021

Version # 04

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or

expense due to improper use.

Revision information Transport Information: Proper Shipping Name/Packing Group

Material name: Dykem® Cross Check™ Torque Seal® - Blue 83318 Version #: 04 Revision date: 06-14-2021 Issue date: 12-30-2020