Strippers

VEW

902-334

ROTARY COAXIAL CABLE STRIPPER

► Fetures:

- Compact and lightweight design for stripping RG-174 coaxial cable easily.
- · Made of ABS handle with SK5 blade
- Rotary stripping, one-squeeze cutting action completely
- Including a small hex wrench in handle for blade depth adjustment.
- Replacement blade: 902-334-BLADES

► Instructions:

Stripping Length:

This stripper can strip cable in four lengths 4,6,8,and 12mm. The stripping length is preset to 8mm. If you want to strip other lengths, you may adjust the blade's position.

Blades' Depth:

You may use the hex wrench, which is install on the bottom of the tool to adjust the blade's depth. Insert the hex wrench into the blade depth adjust on the bottom of the stripper, then rotate the hex wrench clockwise (to cut smaller cable) or counterclockwise (to cut larger cable). Repeat above steps to set the other blade.

Stripping Cable:

- 1. Press the knurled portion on the upper jaw to open the stripper's jaws.
- 2. Insert the cable you want to strip through the V-block until the cable reaches the V-shaped cable guide. Then release the upper jaw to close the jaws.
- 3. Insert your index finger into the stripper's finger ring, turn the stripper clockwise 1-4 times. The cable's insulation is cut while you turn the stripper.
- 4. Open the jaws and remove the cable . Pull away the outer jacket and dielectric to expose the inner conductor.



Rotate for wire stripping



Adjust blade depth





