

## TECHNICAL DATA SHEET

Part#: 7182E

Cutters - 50° Angulated Head - Blade Length .22"  
Offers excellent visibility and accessibility with a larger (.22") blade

The 7182E Lazer Line<sup>®</sup> medium angulated/tapered optimum flush cutter with a cutting capacity of .003" - .025" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. This 6" tool has a 40° angled tip with a set-screw to prevent over-travel while prolonging the life of the tool. The Anti-Static grips are soft cushioned foam and have a surface resistivity of 10<sup>10</sup> ohms/sq. The dual leaf springs provide smooth action.

- Precision Level ★★★★★
- Material Carbon
- Surface Resistivity 10<sup>10</sup> ohms/sq
- Shape Angulated Head
- Type of Cut Optimum Flush
- Cutting Capacity .003 - .025"
- Blade Angle 50°
- Blade Length .22" (5.5mm)
- Body Width 0.42" (10.5mm)
- Body Height 6" (150mm)
- OAL 3
- Weight (OZ) 662847009334
- UPC 8203.20.60.60
- Schedule B EAR99
- ECCN 27111511
- UNSPSC Code USA
- Country of Origin Angled Head
- Group

