

## TECHNICAL DATA SHEET

Part#: 7275E

**Cutters - 50° Angulated Head - Blade Length .16" - Short Handle**  
Offers excellent visibility and accessibility with our smallest angulated (.16") blade

The 7275E Lazer Line<sup>®</sup> miniature angulated/tapered optimum flush cutter with a cutting capacity of .003" - .025" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. This 4.75" tool has 50° angled tips and a set-screw to prevent over travel while prolonging the life of the tool. It features an ergonomically molded antimicrobial Anti-Static grip (10<sup>10</sup> ohms/sq surface resistivity) with dual leaf springs.

• Precision Level	★★★★★
• Material	Carbon
• Surface Resistivity	10 <sup>10</sup> ohms/sq
• Shape	Angulated Head
• Type of Cut	Optimum Flush
• Cutting Capacity	.001" - .018"
• Blade Angle	50°
• Blade Length	.16" (4mm)
• Body Width	0.42" (10.5mm)
• Body Height	.25" (6.35mm)
• OAL	4.75" (118.75mm)
• Weight (OZ)	3
• UPC	662847009679
• Schedule B	8203.20.60.60
• ECCN	EAR99
• UNSPSC Code	27111511
• Country of Origin	USA
• Group	Angled Head

