

TECHNICAL DATA SHEET

Part#: 9248E

Cutters - Medium Taper Relieved Head - Laser Flush
Designed for cutting .030" soft wire leaving no 'pinch' on the wire

The 9248E five star Lazer Line[®] medium tapered/relieved laser flush cutter has a cutting capacity of .001" - .030" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. The CNC machining allows the joint surfaces to be perfect to allow for long life. The dual leaf springs provide smooth action. The Anti-Static grips are soft cushioned foam and have a surface resistivity of 10¹⁰ ohms/sq.

| | |
|-----------------------|---------------------------|
| • Precision Level | ★★★★ |
| • Material | Carbon |
| • Surface Resistivity | 10 ¹⁰ ohms/sq |
| • Shape | Taper Relieved Head |
| • Type of Cut | Lazer Flush |
| • Cutting Capacity | .001 - .030" |
| • Blade Angle | 14.25° |
| • Blade Length | .38" (9.5mm) |
| • Body Width | 0.42" (10.5mm) |
| • Body Height | .25" |
| • OAL | 4.5" (112.5mm) |
| • Weight (OZ) | 3 |
| • UPC | 662847009907 |
| • Schedule B | 8203.20.60.60 |
| • ECCN | EAR99 |
| • UNSPSC Code | 27111511 |
| • Country of Origin | USA |
| • Group | Medium Head - 9200 Series |

