



FLIR CM82/ CM83/CM85

True RMS Power Clamps

FLIR's CM82, CM83 and CM85 industrial-grade power clamp meters are engineered with advanced power analysis and variable frequency drive (VFD) filtering functions required by electrical troubleshooters. The CM83 and CM85 meters offer additional features including Bluetooth technology to connect compatible mobile devices for remote viewing and sharing, and METERLiNK technology, to wirelessly embed electrical readings into radiometric infrared images on compatible FLIR thermal cameras.

Superior accuracy.

Advanced power analysis and variable frequency drive filtering functions

- VFD Mode provides superior accuracy for working on VFD-controlled equipment
- Advanced power efficiency and harmonics measurements for system level performance analysis
- True RMS voltage and current plus non-contact voltage detector

Reliable performance.

Dependable functionality vital to professionals

- 2 meter drop tested with lifetime warranty
- Inrush mode captures fast AC Current spikes during appliance start-up
- Phase Rotation testing ensures the motor and power source are aligned

Key for troubleshooting.

Designed for convenience and ease of use

- Powerful LED lamps assist with clamping and are bright enough to serve as a primary work light
- Remote viewing on smartphones and tablets via Bluetooth plus METERLiNK to wirelessly embed readings into thermal images on compatible FLIR cameras (CM83 and CM85 only)
- Large, easy-to-read digits, backlit display and analog bargraph



Analyze Power-related Issues

Specifications

| Technical Summary | CM82 | CM83 | CM85 | Basic Accuracy |
|---------------------------|------------------------------------|------------------------------------|-------------------------------------|----------------|
| AC/DC Current | 600A | 600A | 1000A | ±2% |
| AC/DC Voltage | 1000V | 1000V | 1000V | ±1% / 0.7% |
| AC VFD Voltage | 1000V | 1000V | 1000V | ±1% |
| Harmonics | 1st-25th Order | 1st-25th Order | 1st-25th Order | ±5% |
| Total Harmonic Distortion | 0.0 to 99.9% | 0.0 to 99.9% | 0.0 to 99.9% | ±3% |
| Inrush Current | 600ACA (Integration Time 100ms) | 600ACA (Integration Time 100ms) | 1000ACA (Integration Time 100ms) | ±3% |
| Active Power | 10kW to 600kW (10V, 5A min) | 10kW to 600kW (10V, 5A min) | 10kW to 1000kW (10V, 5A min) | ±3% |
| Diode Test | 0.4 to 0.8V | 0.4 to 0.8V | 0.4 to 0.8V | ±0.1V |
| Capacitance | 3.999mF | 3.999mF | 3.999mF | ±1.9% |
| Resistance | 99.99kΩ | 99.99kΩ | 99.99kΩ | ±1% |
| Continuity Threshold | 30Ω | 30Ω | 30Ω | ±1% |
| Frequency | 20.00Hz to 9.999kHz | 20.00Hz to 9.999kHz | 20.00Hz to 9.999kHz | ±0.5% |
| Bluetooth Range Max | — | 32ft (10m) | 32ft (10m) | — |
| Jaw Opening | 1.45in (37mm, 1000MCM) | 1.45in (37mm, 1000MCM) | 1.77in (45mm, 1500MCM) | — |
| Category Rating | CAT IV-600V, CAT III-1000V | | | |
| Battery Type | 6 x AAA | | | |
| Warranty | Limited Lifetime* | | | |

* When registered within 60 days of purchase.

Ordering Information

CM82600A True RMS AC/DC Power Clamp with VFD Mode
 CM82-NISTCM82 with Certificate of Traceability to NIST
 CM83600A True RMS AC/DC Power Clamp with VFD Mode and METERLiNK™
 CM83-NISTCM83 with Certificate of Traceability to NIST
 CM851000A True RMS AC/DC Power Clamp with VFD Mode and METERLiNK™
 CM85-NISTCM85 with Certificate of Traceability to NIST

Accessories

TA11.....Protective Case for CM8x and CM7x Series
 TA55.....AC Current Line Splitter
 TA70.....CAT IV Insulated Alligator Clips
 TA80.....CAT IV Silicone Test Leads



Premium silicone test leads included



BOSTON

FLIR Systems, Inc.
 9 Townsend West
 Nashua, NH 03663
 USA
 PH: +1 866.477.3687

BELGIUM

FLIR Commercial
 Systems AB
 Luxemburgstraat 2
 2321 Meer
 Belgium
 PH: +32 (0) 3665 5100

www.flir.com
 NASDAQ: FLIR

PORTLAND

Corporate Headquarters
 FLIR Systems, Inc.
 27700 SW Parkway Ave.
 Wilsonville, OR 97070
 USA
 PH: +1 866.477.3687

CHINA

FLIR Systems (Shanghai)
 Co., Ltd.
 K301-302, No.26 Lane
 16B, Daduhe Road,
 Putuo District, Shanghai
 200062, P.R.China
 PH: +86-21-5169 7628

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2014 FLIR Systems, Inc. All rights reserved. [Created 09/14]