



# Wireless two-way 6 mm (0.24") articulating camera with 1 m (3.3') probe with long focus

## P/N: VSA2-1-W

### Copyright

© 2019, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: VSA2-1-W

Commit: 55937

Language: en-US

Modified: 2019-02-25

Formatted: 2019-07-31

### Website

<http://www.flir.com>

### Customer support

<http://support.flir.com>

### Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



Part No.	VSA2-1-W
<b>General information</b>	
Short description	Wireless two-way 6 mm (0.24") articulating camera with 1 m (3.3') probe with long focus
Compatible main unit	VS70
Integrated handset	Yes
Wireless capabilities	2.4 GHz to main unit
Compatible wireless handset	N/A
Compatible detachable cameras	N/A
Warranty	<a href="https://www.flir.com/testwarranty">https://www.flir.com/testwarranty</a>
<b>Camera specifications</b>	
Articulation	Two-way 240 ± 20° manual tip articulation
Diameter	6 mm
Resolution	VGA ( 640 × 480 pixels)
Probe length	1 m
Focal length	65 mm to Infinity
Field of view	56°
Imaging sensor	CMOS
Video format	NTSC
Brightness control	Manual with variable options
Lamp type	LED
<b>Power system</b>	
Power requirements	Integrated rechargeable battery
Run time	2 hours continuous use
Auto power off	No
Power adapter	100–240 V input/5 V DC output



## Wireless two-way 6 mm (0.24") articulating camera with 1 m (3.3') probe with long focus

P/N: VSA2-1-W

© 2019, FLIR Systems, Inc.

#VSA2-1-W; r. 55937; en-US

<b>Environmental data</b>	
Operating temperature	-10 to 50°C (14–122°F)
Operating humidity	80% maximum
Storage temperature	-40 to 80°C (-40 to 176°F)
<b>Physical data</b>	
Weight	0.43 kg (0.95 lb.)
Dimensions (H × W × L)	190 mm × 70 mm × 63.5 mm (7.5" × 2.75" × 2.5")
Material	PC-ABS, rubber hand grip, nylon strap
Color	Gray, black
<b>Shipping information</b>	
Packaging type	White box with FLIR accessory printing
Packaging contents	White box with FLIR accessory graphic, VSA2-1-W, camera attachments: mirror, anti-snag tip, magnet
Packaging weight	1.3 kg
Packaging dimensions (H × W × L)	43 cm × 37 cm × 7.5 cm
Carton weight	6.2 kg
Carton dimensions (H × W × L)	45 cm × 31 cm × 39 cm
Carton quantity	4
EAN-13	0793950400814
UPC-12	793950400814
Country of origin	TW
Tariff code	9013909000
<b>Technical support</b>	
Website	<a href="http://support.flir.com">http://support.flir.com</a>