

**TECHNICAL DATA** 

## **Wide Angle Infrared Smart Lens**



## **Product overview: Wide Angle Infrared Smart Lens**

When working in a tight space, get a wide field of view that lets you see a larger target from a close distance. See an entire bank of switchgear cabinets in tight quarters, or see more components through an IR window. View the entire side of a building without getting too far away, or inspect roofs quicker than with a standard lens by viewing a much larger area at a time.

Avoid the hassle of sending in your camera to calibrate with the lens — with smart lenses you can just attach the lens to any compatible camera and start taking images.

Made of 100% diamond-turned germanium with an engineered coating, the most efficient available material to transmit energy to the detector.

Compatible with TiX560, TiX520, TiX500, Ti400, Ti300, and Ti200.

### **Specifications: Wide Angle Infrared Smart Lens**

Description	
IFOV (spatial resolution) Ti401 PRO / Ti480 PRO Ti300+ TiX501 / TiX580	1.86 mRad 3.71 mRad 1.86 mRad
Field of view	46 ° H x 34 ° V



ocus distance	15 cm (approximately 6 in)	
---------------	----------------------------	--



# **Ordering information**



#### FLK-LENS/WIDE2

For use with TiX560, TiX520, TiX500, Ti400, Ti300, and Ti200



#### $\textbf{Fluke}. \ \textit{Keeping your world up and running}. \\ \textbf{\textcircled{\$}}$

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2022 Fluke Corporation. Specifications subject to change without notice. 08/2022

Modification of this document is not permitted without written permission from Fluke Corporation.