

**TECHNICAL DATA**

## **9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well**



### **Product overview: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well**

#### 9190A Carrying Case

- Carrying case for the 9190A Ultra-Cool Field Metrology Well
- Dent- and shatter-resistant strong resin case
- Foam lined for impact protection
- Handle and wheels for easy transporting

### **Specifications: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well**

#### **Dimensions**

Exterior: (L x W x D) 24.90 in x 23.70 in x 13.10 in (63.25 cm x 60.2 cm x 33.27 cm)

Interior: (L x W x D) 22.50 in x 21.10 in x 11.40 in (57.15 cm x 53.59 cm x 28.96 cm)

**Weight**

With foam: 27 lbs (12.25 kg)

Without foam: 20.1 lbs (9.12 kg)

**Temperature rating**

-10 °F to +210 °F (-23 °C to +99 °C)

## Ordering information



### **9190-CASE**

Carrying Case, 9190A Ultra-Cool Field Metrology Well

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2025 Fluke Corporation.  
Specifications subject to change without notice.  
04/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**