

**TECHNICAL DATA**

# Fluke CXT280 Extreme Case



## Key features

- Dimensions: 27.9 by 31.8 by 12.7 cm (11 by 12.5 by 5-Inch)
- Buoyancy allows case to float in salt water with 3.6 kg (7.94 lb) load
- Includes an automatic purge valve for quick equalization after changes in atmospheric pressure
- Features an exclusive 6.4 mm (0.25 in) neoprene O-ring and ABS latches for excellent seal

## Product overview: Fluke CXT280 Extreme Case

Unbreakable, watertight, airtight, dustproof, chemical resistant and corrosion proof case.

## Ordering information



### **Fluke-CXT280**

Fluke CXT280 Extreme Case

For use with the following test tools:

- Multimeters: 287, 289
- Earth Ground Testers: 1621

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2022 Fluke Corporation.  
Specifications subject to change without notice.  
11/2022

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**