

TECHNICAL DATA

Fluke STL120 Shielded Test Leads



Key features

- Length: 1.2m (48")
- Bandwidth: 12,5 MHz
- Maximum Signal Voltage: 600V rms. CAT III per IEC 1010-2-031
- Maximum Voltage to Ground: 600V rms. CAT III per IEC 1010-2-031
- Maximum Current: 1A

Product overview: Fluke STL120 Shielded Test Leads

Set of two (one red, one gray) double insulated silicone shielded test leads for noise free measurements. Specially designed for use with the Fluke ScopeMeter 120 Series. Compatible with AC120 Alligator Clips and HC120 Hook Clips. Safety designed ground leads included. Integral strain relieve and extra hard probe tips provide extra long service life. Features safety designed shrouded plugs and notched tip to prevent probe from sliding.

Ordering information



Fluke STL120

Fluke STL120 Shielded Test Leads

Shielded Test Leads



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2022 Fluke Corporation.
Specifications subject to change without notice.
11/2022

**Modification of this document is not permitted
without written permission from Fluke Corporation.**