

REWORK

FR-872 4-BANK IR PREHEATER



The **HAKKO FR-872 4-BANK IR Preheater** includes a feature to control ramp rate for heating sensitive assemblies. Designed to elevate the temperature of printed circuit board assemblies so the components can be soldered and desoldered more easily, with improved results, particularly on high-mass boards, which can "heat-sink" a significant amount of energy from a soldering iron tip or hot air tool. The FR-872 incorporates a new heating method and a closed-loop thermocouple control. The preheater array has four separate switchable zones for smaller PCBs used in devices such as cell phones.

	FEATURES & BENEFITS	SPECIFICATIONS For Part No. FR872-03	
		Power Consumption	1440 W
	High efficiency carbon filament IR heating lamps Judopendent culticable heat sense	Heater Array	Carbon filament lamp X 12
	• 8.8 x 10.5 in (224 x 266 mm) effective heating area	Thermocouple Input	K-type (1)
	 Manual or Auto operation modes Preheat controlled by power percentage or thermocouple for closed-loop feedback of the PCB heating Ramp Control that controls the ramp rate of the PCB when using either of the thermocouple modes of temperature control Soft EPO to protect assemblies 	Power Range	0 - 100% (1% increments)
		Temperature Range	120 F° - 392 °F / 50 °C - 200 °C
		Ramp Rate Select	34, 36, or 37 °F/sec
	Automatic operation following a 3-heating zone profile that con he programmed into the system (with use 20 appril)	Timer Range	0 - 999 seconds
	 Faster than ceramic IR heating Integration capability with the Hakko FR-803B hot air and FM-206 rework systems with connecting cable (B3657 and B3686 (Not included)). 	Operating Modes	Manual - Power Manual - Thermocouple Automatic - Power Automatic - Thermocouple
		Heating Control	Power: Percentage-based Thermocouple: PID control
	FR-872	Maximum Board Depth	16.9 in. / 430 mm
		Dimensions (W x H x D)	14.2 x 3.8 x 21.1 in. / 360 x 97 x 535 mm
		Heating Area (W x D)	11.2 x 13.8 in. / 286 x 350 mm
	P/N: FR872-03	Effective Heating Area (W x D)	8.8 x 10.5 in. / 224 x 266 mm
<u>4</u> 28	And	Zones	4
ll 🙀		External Connections	1 — integrate with the FM-206
CONTENTS For Part No. FR872-03			R872-03
-		Part No.	Description
		A5003 B3516 B5042 	FR-872 4-bank ir preheater High efficiency carbon filament ir heater (spare) Thermocouple (2) nuts (2) washers Power cord Instruction manual
			For more information Scan OR Code.