

Specification Sheet

Part Number: T40IOM4



- Engineered and manufactured for maximum performance and quality.
- Made from 100% high-quality plastic to ensure efficient recycling.
- Inside serration for a strong grip onto bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail allows for simpler insertion.

Cable Tie, 11" Long, UL Rated, 40lb Tensile Strength, PA66, Black, 1000/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                              |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 111-04604                                                                                                                                                                                                                                                                                                                                                    |
| Type                | T40I                                                                                                                                                                                                                                                                                                                                                         |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                                   |
| Quantity Per        | pack                                                                                                                                                                                                                                                                                                                                                         |
| Product Description | T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description   | Cable Tie, 11" Long, UL Rated, 40lb Tensile Strength, PA66, Black, 1000/pkg                                                                                                                                                                                                                                                                                  |

|                                     |                      |
|-------------------------------------|----------------------|
| Global Part Name                    | T40I-PA66-BK         |
| Minimum Tensile Strength (Imperial) | 40                   |
| Minimum Tensile Strength (Metric)   | 180                  |
| Length L (Imperial)                 | 11.61                |
| Length L (Metric)                   | 295.0                |
| Identification Plate Position       | none                 |
| Releasable Closure                  | No                   |
| Variant                             | Inside Serrated      |
| Width W (Imperial)                  | 0.16                 |
| Width W (Metric)                    | 4.0                  |
| Bundle Diameter Min (Imperial)      | 0.06                 |
| Bundle Diameter Min (Metric)        | 1.5                  |
| Bundle Diameter Max (Imperial)      | 3.15                 |
| Bundle Diameter Max (Metric)        | 80.0                 |
| Material                            | Polyamide 6.6 (PA66) |

|                               |                                  |
|-------------------------------|----------------------------------|
| Material Shortcut             | PA66                             |
| Flammability                  | UL 94 V-2                        |
| Halogen Free                  | Yes                              |
| UV Resistant (Yes/No)         | No                               |
| Use Conditions                | For Indoor and Outdoor Use       |
| Plenum Rating                 | AH-2                             |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)  | Yes                              |
| ROHS Compliant                | Yes                              |
| Certification/Specification   | UL 62275                         |
| UL Recognized (US)            | Yes                              |
| UL Listed (US and Canada)     | Yes                              |
| UL Recognized (US and Canada) | Yes                              |
| UL Listed (US)                | Yes                              |
| Package Quantity (Imperial)   | 1000                             |
| Package Quantity (Metric)     | 1000                             |

Customs Number

3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)