

## Specification Sheet

Part Number: CTT60R6M4



Head design contains clamping rails to provide full circumferential compression around bundles.

Bent tail allows for quick insertion into head.

Clamp Tie, 8" Long, 60lb Tensile Strength, PA66, Blue, 1000/pkg

Article Number 112-52103

Type CTT60R

Color Blue (BU)

Quantity Per pack

Product Description HellermannTyton clamp tie has triangular shaped tabs extending beneath the head for optimal surface contact and complete circumferential compression to 360 degrees. The bent tail design allows quick and simple installations by hand. The clamps are recommended for soft rubber hose applications including fuel, water, and air vacuum lines.

Short Description Clamp Tie, 8" Long, 60lb Tensile Strength, PA66, Blue, 1000/pkg

Global Part Name CTT60R-PA66-BU

|                                     |                 |
|-------------------------------------|-----------------|
| Minimum Tensile Strength (Imperial) | 60              |
| Minimum Tensile Strength (Metric)   | 267             |
| Length L (Imperial)                 | 8.0             |
| Length L (Metric)                   | 203.2           |
| Identification Plate Position       | none            |
| Releasable Closure                  | No              |
| Tie Closure                         | plastic pawl    |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.19            |
| Width W (Metric)                    | 4.7             |
| Bundle Diameter Min (Imperial)      | 0.06            |
| Bundle Diameter Min (Metric)        | 1.5             |
| Bundle Diameter Max (Imperial)      | 1.77            |
| Bundle Diameter Max (Metric)        | 45.0            |
| Thickness T (Metric)                | 1.2             |

|                               |                                  |
|-------------------------------|----------------------------------|
| Material                      | Polyamide 6.6 (PA66)             |
| Material Shortcut             | PA66                             |
| Flammability                  | UL 94 V-2                        |
| UV Resistant (Yes/No)         | No                               |
| Use Conditions                | For Indoor Use Only              |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)  | Yes                              |
| ROHS Compliant                | Yes                              |
| Certification/Specification   | UL                               |
| UL Recognized (US)            | Yes                              |
| UL Recognized (US and Canada) | Yes                              |
| Package Quantity (Imperial)   | 1000                             |
| Package Quantity (Metric)     | 1000                             |
| Customs Number                | 3926909988                       |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Privacy Policy](#)

[Cookie Policy](#)

[Terms and Conditions](#)