

Specification Sheet

Part Number: 156-01641

Updated 9x17mm oval fir tree design maintains bundle orientation.

Fir tree provides low insertion force with high extraction resistance, for easy assembly and reliable performance.

Disc feature prevents rattling in high-vibration applications and protects against debris ingress.



Dual Cable Ties with Oval Fir Tree Mount, 8.0" Long, 9.0 x 17.0 mm Mounting Hole, 50lb, PA66HIRHSUV, Black, 500/bag

Article Number	156-01641
----------------	-----------

Type	T50RFT9X17B2
------	--------------

Color	Black (BK)
-------	------------

Quantity Per	pack
--------------	------

Product Description	These two-piece fasteners are pre-assembled and offer a simple and versatile method of bundling and mounting cables running perpendicular to 9x17 oval mounting holes. The fir tree base will easily push into pre-punched holes in panels or threaded blind holes and offers a secure fit. The two-piece design enables the head of the tie to be oriented to the required position to ease assembly, while the disc on top of the fir tree covers the hole and minimizes the ingress of water and dirt.
---------------------	---

Short Description	Dual Cable Ties with Oval Fir Tree Mount, 8.0" Long, 9.0 x 17.0 mm Mounting Hole, 50lb, PA66HIRHSUV, Black, 500/bag
Global Part Name	T50RFT9X17B2-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.0
Length L (Metric)	203.2
Fixation Method	Fir Tree for oval holes
Identification Plate Position	none
Tie Closure	plastic pawl
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.2
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Cable Tie Head Length (Imperial)	0.29

Cable Tie Head Width (Imperial)	0.3
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.22
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	5.5
Mounting Hole Diameter D (Imperial)	0.35 x 0.67 "
Mounting Hole Diameter D (Metric)	9.0 x 17.0 mm

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Foot Part Material	PA66HIRHS
Material Shortcut	PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Operating Temperature intermittant, 1000 hours	+320°F (+160°C)
Operating Temperature intermittant, 5000 hours	+257°F (+125°C)

Operating Temperature intermittent, 500 hours	+329°F (+165°C)
---	-----------------

Reach Compliant (Article 33)	Yes
------------------------------	-----

ROHS Compliant	Yes
----------------	-----

Package Quantity (Imperial)	3000
-----------------------------	------

Package Quantity (Metric)	500
---------------------------	-----

Customs Number	3926909988
----------------	------------

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)