

## Specification Sheet


Part Number: 156-04005

Pre-assembled 2-piece self-affixing tie with coupler

Cable tie head can be moved after bundling

Easy addition of cables after assembly

For parallel routing of bundles that can be twisted 90° even after installation



3-Piece T50R Tie with Coupler, 8" Long, 0.08" - 1.97" Dia, 50lbs, PA46, Gray, 500/bg

Article Number

156-04005

Type

T50RCOUPLER

Color

Gray (GY)

Quantity Per

pack

Product Description

The Coupler is the simple way to connect two cable ties for a parallel routing of two bundles. His special design allows the ties 90 degrees of rotation. This is ideal for all applications where the cable, pipe or hose should move flexible in relation to the fixing point. The Coupler can be used with one or two cable ties. This allows easily subsequent installation or replacements of further cables, pipes or hose.

Short Description

3-Piece T50R Tie with Coupler, 8" Long, 0.08" - 1.97" Dia, 50lbs, PA46, Gray, 500/bg

|                  |                     |
|------------------|---------------------|
| Global Part Name | T50RCOUPLER-PA46-GY |
|------------------|---------------------|

|                                     |    |
|-------------------------------------|----|
| Minimum Tensile Strength (Imperial) | 50 |
|-------------------------------------|----|

|                                   |     |
|-----------------------------------|-----|
| Minimum Tensile Strength (Metric) | 225 |
|-----------------------------------|-----|

|                     |       |
|---------------------|-------|
| Length L (Imperial) | 7.874 |
|---------------------|-------|

|                   |       |
|-------------------|-------|
| Length L (Metric) | 202.0 |
|-------------------|-------|

|                               |      |
|-------------------------------|------|
| Identification Plate Position | none |
|-------------------------------|------|

|             |              |
|-------------|--------------|
| Tie Closure | plastic pawl |
|-------------|--------------|

|         |                 |
|---------|-----------------|
| Variant | Inside Serrated |
|---------|-----------------|

|                    |      |
|--------------------|------|
| Width W (Imperial) | 0.18 |
|--------------------|------|

|                  |     |
|------------------|-----|
| Width W (Metric) | 4.6 |
|------------------|-----|

|                                |      |
|--------------------------------|------|
| Bundle Diameter Min (Imperial) | 0.08 |
|--------------------------------|------|

|                              |     |
|------------------------------|-----|
| Bundle Diameter Min (Metric) | 2.0 |
|------------------------------|-----|

|                                |      |
|--------------------------------|------|
| Bundle Diameter Max (Imperial) | 1.85 |
|--------------------------------|------|

|                              |      |
|------------------------------|------|
| Bundle Diameter Max (Metric) | 47.0 |
|------------------------------|------|

|                                         |      |
|-----------------------------------------|------|
| Bundle Diameter 1st Loop Max (Imperial) | 1.97 |
|-----------------------------------------|------|

|                                       |      |
|---------------------------------------|------|
| Bundle Diameter 1st Loop Max (Metric) | 50.0 |
|---------------------------------------|------|

|                                         |                                   |
|-----------------------------------------|-----------------------------------|
| Bundle Diameter 2nd Loop Max (Imperial) | 1.97                              |
| Bundle Diameter 2nd Loop Max (Metric)   | 50.0                              |
| Height H (Imperial)                     | 0.33                              |
| Height H (Metric)                       | 8.3                               |
| Cable Tie Width Max (Imperial)          | 0.185                             |
| Cable Tie Width Max (Metric)            | 4.70                              |
| Material                                | Polyamide 4.6 (PA46)              |
| Foot Part Material                      | PA46                              |
| Material Shortcut                       | PA46                              |
| Material Cable Tie                      | Polyamide 4.6 (PA46)              |
| Flammability                            | UL 94 V-2                         |
| UV Resistant (Yes/No)                   | No                                |
| Use Conditions                          | For Indoor Use Only               |
| Operating Temperature                   | -40°F to +266°F (-40°C to +130°C) |
| ROHS Compliant                          | Yes                               |

|                             |            |
|-----------------------------|------------|
| Package Quantity (Imperial) | 500        |
| Package Quantity (Metric)   | 500        |
| Customs Number              | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)