

Specification Sheet

Part Number: 156-04047



Anti-rotation pin eliminates movement of bundle when fastening bolt.
Heavy duty mount with robust 120 lb tie delivers an ultra strong alternative to metal clamps.

Assembly withstands vibrations and displacement forces.

Metal bushing accommodates high tightening torque.

2-Piece Cable Tie/Screw Mount, 15" Long, M6 Hole, 4.1" Max Bundle Dia, 120lb, PA66HIRHS, BK/OG, 2500/ctn

Article Number	156-04047
Type	T120RCPCM6-TSSET
Color	Black (BK) Orange (OG), High Voltage (HV)
Quantity Per	carton
Product Description	HellermannTyton Heavy Duty Fir Tree Mounts are designed with extreme applications in mind. They are optimized for up to 3-to-1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.
Short Description	2-Piece Cable Tie/Screw Mount, 15" Long, M6 Hole, 4.1" Max Bundle Dia, 120lb, PA66HIRHS, BK/OG, 2500/ctn
Global Part Name	T120RCPCM6-TSSET-PA66HIRHS-OG/BK

Minimum Tensile Strength (Imperial)	120.0
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	14.96
Length L (Metric)	42.6
Fixation Method	Screw Mount
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.87
Width W (Metric)	20.0
Bundle Diameter Min (Imperial)	0.20
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	4.13
Bundle Diameter Max (Metric)	105.0
Height H (Imperial)	0.92

Height H (Metric)	23.5
Cable Tie Width Max (Imperial)	0.3
Mounting Hole Diameter D (Metric)	M6
Stud Diameter (Metric)	6.0 mm
Stud Diameter (Imperial)	0.24
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Material Cable Tie	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Flammability	UL 94 HB
Halogen Free	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	2500
Package Quantity (Metric)	2500
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)