

Specification Sheet

Part Number: 156-04083



Pre-assembled 2-piece cable tie with fir tree provides the convenience of bundling and mounting with one part.

Cable tie head can be reoriented around bundle to avoid obstructions or chafing nearby bundles.

Easy to assemble without the need for a tool.

Disc stabilizes mount and minimizes debris ingress.

Fir tree can be used for a variety of panel thicknesses, threaded or not.

2-Pc Cable Tie/Fir Tree Mount, 8.0"L, 6.1-7.0mm Mounting Hole Dia, PA66HIRHSUV, BK, 1000/CTN

Article Number

156-04083

Type

T50RX2DUALSDFT6.5A

Color

Black (BK)

Quantity Per

carton

Product Description

These three-piece self-affixing cable ties are supplied ready assembled and offer a simple and versatile method of bundling and fastening cables. The deep-hole anchor will easily push into blind holes with or without thread and offers a very secure attachment. The two-piece design enables the head of the tie to be oriented to the required position to ease assembly, while the disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description	2-Pc Cable Tie/Fir Tree Mount, 8.0"L, 6.1-7.0mm Mounting Hole Dia, PA66HIRHSUV, BK, 1000/CTN
Global Part Name	T50RX2DUALSDFT6.5A-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.0
Length L (Metric)	203.2
Fixation Method	Fir tree for round holes
Identification Plate Position	none
Tie Closure	plastic pawl
Width W (Imperial)	0.46
Width W (Metric)	11.7
Bundle Diameter Min (Imperial)	0.6
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.9
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.80

Height H (Metric)	20.5
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.23
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.28
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL 94 HB
Halogen Free	Yes

UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)