


Specification Sheet

Part Number: 156-04238



These assemblies consist of two cable ties and a weld stud mounting base - supplied pre-assembled for ease and speed of installation. It features a 'soft-push' design - no tools are required to fit the parts to the stud.

Ideal for installation onto the stud prior to attaching the cable, since there are no lateral tolerances required.

3-Piece M5/T5/M6/T6 Stud Mount Ties, 8" L, 50lb Tensile Strength, PA66HS/PA66HIRHS, BK, 500/pkg

Article Number	156-04238
Type	T50ROSEX2SBS5-6U
Color	Black (BK)
Quantity Per	bag
Product Description	Three-piece design enables up to two separate bundles to be fastened to the same stud. The preassembled part provides ease of installation. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications.
Short Description	3-Piece M5/T5/M6/T6 Stud Mount Ties, 8" L, 50lb Tensile Strength, PA66HS/PA66HIRHS, BK, 500/pkg

Global Part Name	T50ROX2SBS5-6U-PA66HS/PA66HIRHSUV-BK
------------------	--------------------------------------

Minimum Tensile Strength (Imperial)	50
-------------------------------------	----

Minimum Tensile Strength (Metric)	200
-----------------------------------	-----

Length L (Imperial)	7.95
---------------------	------

Length L (Metric)	202.0
-------------------	-------

Fixation Method	Stud Mount
-----------------	------------

Identification Plate Position	none
-------------------------------	------

Tie Closure	plastic pawl
-------------	--------------

Width W (Imperial)	0.18
--------------------	------

Width W (Metric)	4.6
------------------	-----

Bundle Diameter Min (Imperial)	0.16
--------------------------------	------

Bundle Diameter Min (Metric)	4.0
------------------------------	-----

Bundle Diameter Max (Imperial)	1.97
--------------------------------	------

Bundle Diameter Max (Metric)	50.0
------------------------------	------

Height H (Imperial)	0.05
---------------------	------

Height H (Metric)	1.2
-------------------	-----

Stud Diameter (Metric)	M5 M6
Stud Diameter (Imperial)	0.20
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV PA66HS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)