

## Specification Sheet

Part Number: 169-60132

Excellent flame-resistant properties with higher operating temperature ranges for a wider range of application environments.

High-visibility orange color offers safe identification of high-voltage cabling.

Lateral slit allows for fast and easy insertion, inspection and future access to cabling.

The UV additive prevents damage and discoloration caused by long-term exposure to sunlight.



Convoluted Tubing, Slit, 0.38" Dia, PP-FR-UV, Orange, 1800 ft/carton

|                |                                |
|----------------|--------------------------------|
| Article Number | 169-60132                      |
| Type           | CTPPFRUV380                    |
| Color          | Orange (OG), High Voltage (HV) |
| Quantity Per   | carton                         |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description            | HellermannTyton's Orange Flame-Retardant Polypropylene with UV Inhibitor Convuluted Slit Tubing provides high visibility, is self-extinguishing and offers elevated protection against UV radiation for long-term outdoor use. Convuluted tubing efficiently protects wire harness assemblies, hoses and cables against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires while reducing the chance of installation damage. Its unique blend of flame-retardant polypropylene is suitable for applications requiring self-extinguishing materials and complies with UL 94 V-2 standards. |
| Short Description              | Convuluted Tubing, Slit, 0.38" Dia, PP-FR-UV, Orange, 1800 ft/carton                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Global Part Name               | CTPPFRUV380-PPFRUV-OG                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Bundle Diameter Min (Imperial) | 0.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Bundle Diameter Min (Metric)   | 1.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Bundle Diameter Max (Imperial) | 0.38                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Bundle Diameter Max (Metric)   | 9.7                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Inner Diameter D (Imperial)    | 0.380                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Inner Diameter D (Metric)      | 9.65                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Diameter D (Imperial)          | 0.526                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Diameter D (Metric)            | 13.36                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Outside Diameter OD (Imperial) | 0.526                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Outside Diameter OD (Metric)   | 13.36                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                              |                                                        |
|------------------------------|--------------------------------------------------------|
| Nominal Diameter (Imperial)  | 3/8                                                    |
| Nominal Diameter (Metric)    | 9.65                                                   |
| Wall Thickness WT (Imperial) | 0.005                                                  |
| Wall Thickness WT (Metric)   | 0.127                                                  |
| Material                     | Polypropylene, flame retardant, UV-stabilized (PPFRUV) |
| Material Shortcut            | PPFRUV                                                 |
| Flammability                 | UL 94 V-2                                              |
| Halogen Free                 | No                                                     |
| UV Resistant (Yes/No)        | Yes                                                    |
| Use Conditions               | For Indoor and Outdoor Use                             |
| Operating Temperature        | -40°F to +257°F (-40°C to +125°C)                      |
| Reach Compliant (Article 33) | Yes                                                    |
| ROHS Compliant               | Yes                                                    |
| Package Quantity (Imperial)  | 1800                                                   |
| Package Quantity (Metric)    | 548.64                                                 |

Customs Number

3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)