HellermannTyton

Specification Sheet

Part Number: 170-01161

Self-wrapping woven sleeving made of fiberglass and PET polyester protects against chewing damage.

Provides good protection against abrasion, UV and weathering, vibration and impact.

Quick and easy installation and removal, ideal for retrofitting.

Lightweight material won't add significant weight to the installation.

Resists acids, solvents and micro-organisms for extended performance in industrial environments.

Braided Sleeving, Twist-In Rodent-Repellant Wrap, 13mm Dia. FG/PET, White, 164 ft/rl

Article Number	170-01161
Туре	Twist-In-RR-13
Color	Black (BK) White (WH)
Quantity Per	reel
Product Description	Twist-In Rodent-Repellent Wrap is a self-closing fiberglass sleeving used to bundle cables and hoses and protect against rodents in infestation-prone areas such as automotive, railways, telecom, underground and waste treatment systems.
Short Description	Braided Sleeving, Twist-In Rodent-Repellant Wrap, 13mm Dia. FG/PET, White, 164 ft/rl



Bundle Diameter Min (Imperial)	0.39
Bundle Diameter Min (Metric)	10
Bundle Diameter Max (Imperial)	0.51
Bundle Diameter Max (Metric)	13
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	12.7
Wall Thickness WT (Metric)	0.8

Material	Polyester (PET) Glass Fiber (GF)		
Material Shortcut	PET GF		
Flammability	FMVSS 302		
Halogen Free	Yes		
UV Resistant (Yes/No)	Yes		
Operating Temperature	-94°F to +257°F (-70°C to +125°C)		
Reach Compliant (Article 33)	Yes		

ROHS Compliant	Yes	
Certification/Specification	EN [45545-2]	
Package Quantity (Imperial)	164.0	
Package Quantity (Metric)	50	
Customs Number	7019901100	
Reel Weight (Imperial)	4.41	
Reel Weight (Metric)	2.0	

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.			
Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions