HellermannTyton

Specification Sheet

Part Number: 181-15420



Strong fingers prevent unwanted breaking.

Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.

Supplied with mounting holes to streamline installation.

Optional covers enhance protection and appearance.

Slotted Wall Wiring Duct, 1.5" x 4", Non-Adhesive, PVC, Gray, 140ft/Carton

Article Number 181-15420

Type SL1.5X4

Color Gray (GY)

Quantity Per box

Product Description HellermannTyton Slotted Wall Wiring Duct features break-away fingers

that provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line

allows the sidewall to be smoothly cut for joints and T's.

Short Description Slotted Wall Wiring Duct, 1.5" x 4", Non-Adhesive, PVC, Gray,

140ft/Carton

Global Part Name SL1.5X4-PVC-GY

Length L (Imperial)	6.0
Length L (Metric)	1.83
Fixation Method	Non-Adhesive
Width W (Imperial)	1.50
Width W (Metric)	38.10
Height H (Imperial)	4.07
Height H (Metric)	103.4
Mounting Hole Centers (Imperial)	4.0
Material	
	Polyvinylchloride - rigid extrusion grade (PVC)
Material Shortcut	Polyvinylchloride - rigid extrusion grade (PVC) PVC
Material Shortcut Operating Temperature	
	PVC
Operating Temperature	PVC +122°F (+50°C)

140

Package Quantity (Imperial)

Customs Number	392590	00000		
About HellermannTyton				
HellermannTyton is a global manufactor electrical, construction, industrial autor to product design, sustainability, product customers. HellermannTyton operates (www.hellermann.tyton.com).	mation, broadb action, quality a	and and other OEM markets. assurance and delivery is opting	The company' nized to benefi	s integrated approach it local and global
© 2024 HellermannTyton. All Rights	Reserved. Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions

42.7

Package Quantity (Metric)