

## Specification Sheet

Part Number: 104-10103

Genuine Metabo CAS 18v 2.0 Ah Li-Ion battery for ProCut tools.

Cordless operation delivers up to 2,000 tool cycles on a single charge.

CAS batteries are compatible with a range of industrial power tool brands, so they are interchangeable as needed.



CAS Lithium-Ion Battery, 18V, 2Ah, 36Wh for Tools, Plastic, Black, 1/pkg

|                     |                                                                                                                               |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 104-10103                                                                                                                     |
| Type                | SP-ProCut9Battery                                                                                                             |
| Color               | Black (BK)                                                                                                                    |
| Quantity Per        | box                                                                                                                           |
| Product Description | The Metabo CAS lithium-ion battery is an 18v, 2.0 Ah power source for HellermannTyton's ProCut and CPK Hybrid portable tools. |
| Short Description   | CAS Lithium-Ion Battery, 18V, 2Ah, 36Wh for Tools, Plastic, Black, 1/pkg                                                      |
| Global Part Name    | SP-ProCut9Battery-PL-BK                                                                                                       |

|                              |                                   |
|------------------------------|-----------------------------------|
| Tension Setting Tools        | Adjustable                        |
| Material                     | Plastic (PL)                      |
| Material Shortcut            | PL                                |
| UV Resistant (Yes/No)        | No                                |
| Use Conditions               | For Indoor and Outdoor Use        |
| Operating Temperature        | -40°F to +257°F (-40°C to +125°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 1                                 |
| Package Quantity (Metric)    | 1                                 |
| Customs Number               | 8507600000                        |