

Specification Sheet

Part Number: 111-01266



Nylon 11 cable ties provide excellent resistance to UV, chemical and moisture sensitive environments
Inside serrations and smooth edges allow for a strong grip on cables and wire bundles without damaging them
Head design provides high tensile strength with very low insertion force

Article Number	111-01266
Type	GL300
Color	Black (BK)
Quantity Per	bag
Product Description	These inside serrated cable ties are manufactured from Polyamide 11 that provides excellent UV, chemical, and moisture resistance to allow for a longer life span in outdoor use. This material is recommended for applications exposed to metal oxides. The head design guarantees high tensile strength, as well as a low insertion force. Tensioning tools are available to ensure consistent and safe installation.
Short Description	Solar Tie, 11.9" Long, 56lb Tensile Strength, PA11W, Black, 100/pkg

Global Part Name	GL300-PA11UV-BK
------------------	-----------------

Minimum Tensile Strength (Imperial)	56
-------------------------------------	----

Minimum Tensile Strength (Metric)	250
-----------------------------------	-----

Length L (Imperial)	11.9
---------------------	------

Length L (Metric)	302.26
-------------------	--------

Identification Plate Position	none
-------------------------------	------

Releasable Closure	No
--------------------	----

Tie Closure	plastic pawl
-------------	--------------

Variant	Inside Serrated
---------	-----------------

Width W (Imperial)	0.19
--------------------	------

Width W (Metric)	4.8
------------------	-----

Bundle Diameter Min (Imperial)	0.28
--------------------------------	------

Bundle Diameter Min (Metric)	7.0
------------------------------	-----

Bundle Diameter Max (Imperial)	3.2
--------------------------------	-----

Bundle Diameter Max (Metric)	80.0
------------------------------	------

Thickness T (Metric)	1.5
----------------------	-----

Material	Polyamide 11, UV-resistant (PA11UV)
Material Shortcut	PA11UV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	IEC 62275:2018
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988