

Specification Sheet

Part Number: 111-15210



- Engineered and manufactured for maximum performance and quality. Made from 100% high-quality plastic to ensure efficient recycling.
- Inside serration for a strong grip onto bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail allows for simpler insertion.
- Complies with MS3367-3-0, Class 2 and SAE-AS33671.

Heavy Duty MilSpec Cable Tie, 15" Long, MS3367, 175lb Tensile Strength, PA66UV, Black, 25/bag

|                |            |
|----------------|------------|
| Article Number | 111-15210  |
| Type           | T150R      |
| Color          | Black (BK) |
| Quantity Per   | box        |

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description                 | Used in the solar industry and other applications, HellermannTyton offers cable ties made of UV stabilized PA66UV material. This material provides additional protection against UV radiation for long-term outdoor use and is available in various styles, tensile strengths, and bundle diameters. T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. Specially manufactured to comply with Military Specification MS3367-3-0, Class 2 and SAE-AS33671. |
| Short Description                   | Heavy Duty MilSpec Cable Tie, 15" Long, MS3367, 175lb Tensile Strength, PA66UV, Black, 25/bag                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Global Part Name                    | T150R-PA66UV-BK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Minimum Tensile Strength (Imperial) | 175                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Minimum Tensile Strength (Metric)   | 780                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Length L (Imperial)                 | 15.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Length L (Metric)                   | 390.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Identification Plate Position       | none                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Releasable Closure                  | No                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Variant                             | Inside Serrated                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Width W (Imperial)                  | 0.35                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Width W (Metric)                    | 8.9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

|                                |                                      |
|--------------------------------|--------------------------------------|
| Bundle Diameter Min (Imperial) | 0.31                                 |
| Bundle Diameter Min (Metric)   | 8.0                                  |
| Bundle Diameter Max (Imperial) | 4.13                                 |
| Bundle Diameter Max (Metric)   | 105.0                                |
| Thickness T (Imperial)         | 0.07                                 |
| Thickness T (Metric)           | 1.9                                  |
| Material                       | Polyamide 6.6 UV-stabilized (PA66UV) |
| Material Shortcut              | PA66UV                               |
| US MIL SPEC                    | MS3367-3-0, Class 2<br>SAE-AS33671   |
| Flammability                   | UL 94 V-2                            |
| Halogen Free                   | Yes                                  |
| UV Resistant (Yes/No)          | Yes                                  |
| Operating Temperature          | -40°F to +185°F (-40°C to +85°C)     |
| Reach Compliant (Article 33)   | No                                   |
| ROHS Compliant                 | Yes                                  |

|                             |          |
|-----------------------------|----------|
| Certification/Specification | UL 62275 |
|-----------------------------|----------|

|                    |     |
|--------------------|-----|
| UL Recognized (US) | Yes |
|--------------------|-----|

|                               |     |
|-------------------------------|-----|
| UL Recognized (US and Canada) | Yes |
|-------------------------------|-----|

|                             |    |
|-----------------------------|----|
| Package Quantity (Imperial) | 25 |
|-----------------------------|----|

|                           |    |
|---------------------------|----|
| Package Quantity (Metric) | 25 |
|---------------------------|----|

|                |            |
|----------------|------------|
| Customs Number | 3926909988 |
|----------------|------------|

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)