

Specification Sheet

Part Number: T50SL7.NN6P

Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

Arrowhead style mount provides low insertion and high extraction force.

Arrowhead disc protects against dirt and other impurities.



1-Piece Cable Tie/Arrowhead Mount w/Wings, 6.5"L, 50lb, 0.27 - 0.28" Hole Dia, PA66, Natural, 500/bg

Article Number 111-85479

Type T50SL7

Color Natural (NA)

Quantity Per bag

Product Description
Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description
1-Piece Cable Tie/Arrowhead Mount w/Wings, 6.5"L, 50lb, 0.27 - 0.28" Hole Dia, PA66, Natural, 500/bg

Global Part Name T50SL7-PA66-NA

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 6.5

Length L (Metric) 165

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 1.34

Bundle Diameter Max (Metric) 34.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Height H (Imperial)	0.4
Height H (Metric)	10.0
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.10
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	2.5
Mounting Hole Diameter D (Imperial)	0.27 - 0.28
Mounting Hole Diameter D (Metric)	6.9 - 7.1 mm
Mounting Hole Diameter D Min (Imperial)	0.27
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.1
Disc Diameter (Imperial)	0.73

Material Polyamide 6.6 (PA66)

Material Shortcut	PA66
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988