HellermannTyton

Specification Sheet

Part Number: 111-95339

316 grade stainless steel offers excellent resistance to salt spray, corrosion, weather and chemical resistance.

Self locking, ball bearing mechanism for quick and easy installation, either by hand or by tensioning tool.

Fully enclosed head prevents dirt or grit from interfering with locking mechanism.

High tensile strength for maximum strength and safety on heavy duty applications.



Stainless Steel Tie, 33" Long, 607lb Tensile Strength, SS316, Metal, 50/pkg

Article Number 111-95339

Type MBT33XH

Color Metal (ML)

Quantity Per pcs.

Product Description	HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes, and more. Stainless steel ties can be used in virtually any indoor, outdoor, or underground application. Grade 316 material is highly resistant to corrosion and widely used in marine environments where chemicals, salts, acids, and temperature extremes may affect the bundling application. MBT stainless steel ties in 316 stainless steel material are also available with a polyester protective coating. This coating creates a barrier and protectant from chemical reactions of dissimilar metals.
Short Description	Stainless Steel Tie, 33" Long, 607lb Tensile Strength, SS316, Metal, 50/pkg
Global Part Name	MBT33XH-SS316-ML
Minimum Tensile Strength (Imperial)	607.0
Minimum Tensile Strength (Metric)	2700.0
Length L (Imperial)	33.0

838.0

none

No

ball bearing lock

Not Serrated

0.48

Length L (Metric)

Releasable Closure

Width W (Imperial)

Tie Closure

Variant

Identification Plate Position

Width W (Metric)	12.3
Bundle Diameter Min (Imperial)	0.47
Bundle Diameter Min (Metric)	12.0
Bundle Diameter Max (Imperial)	10.0
Bundle Diameter Max (Metric)	254.0
Thickness T (Imperial)	0.01
Thickness T (Metric)	0.3
Cable Tie Head Length (Imperial)	0.55
Cable Tie Head Width (Imperial)	0.57
Material	Stainless Steel (SS316)
Material Shortcut	SS316
Flammability	Non-burning
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)

ROHS Compliant
Yes

Certification/Specification
Bureau Veritas | IEC 60092

Package Quantity (Imperial)
50

Package Quantity (Metric)
50

Customs Number
7326908695

Yes

© 2023 HellermannTyton. All Rights Reserved.

Reach Compliant (Article 33)

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions