

Specification Sheet

Part Number: 133-02353



Bundling clip with gradual transition provides security to bundles around panel edges.
Flanged ends prevent slip in tape wrap.
4x oval prevents bundle rotation while providing best-in-class installation and extraction resistance for four common oval sizes.

Angled Bundling Clip, 65mm Long, 0.60 - 6.75mm Panel Thickness, PA66HIRHSUV, Black, 4000/ctn

Article Number	133-02353
Type	FTOVALSTRNRLF
Color	Black (BK)
Quantity Per	carton
Product Description	Designed for use with cable ties or electrical tape, bundling clips provide a simple method of securing wire and cable bundles. HellermannTyton offers these clips in standard and standoff orientations, with a variety of mounting options.
Short Description	Angled Bundling Clip, 65mm Long, 0.60 - 6.75mm Panel Thickness, PA66HIRHSUV, Black, 4000/ctn
Global Part Name	FTOVALSTRNRLF-PA66HIRHSUV-BK

Length L (Imperial)	2.55
Length L (Metric)	64.7
Fixation Method	Fir Tree
Height H (Imperial)	0.89
Height H (Metric)	22.6
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.26" x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 12.5 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB

Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988