

Specification Sheet

Part Number: 151-00513



HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.

An assortment of Connector Cips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Conn. Clip w/Oval Arrowhead, 0.6-1.0mm Panel Thick, 6.2x12.2 mm Hole Dia, PA66HIRHS, Black, 500/pkg

Article Number 151-00513

Type YCCSFT62122

Color Black (BK)

Quantity Per bag

Product Description

Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description	Conn. Clip w/Oval Arrowhead, 0.6-1.0mm Panel Thick, 6.2x12.2 mm Hole Dia, PA66HIRHS, Black, 500/pkg		
Global Part Name	YCCSFT62122-PA66HIRHS-BK		
Length L (Metric)	27.5		
Fixation Method	Arrowhead for oval holes		
Width W (Metric)	16.0		
Height H (Metric)	14.1		
Panel Thickness Min (Imperial)	0.02		
Panel Thickness Max (Imperial)	0.04		
Panel Thickness Min (Metric)	0.6		
Panel Thickness Max (Metric)	1.0		
Mounting Hole Diameter D (Imperial)	0.24 - 0.48		
Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm		
Mounting Hole Diameter D Min (Imperial)	0.24		

0.48

12.2

Mounting Hole Diameter D Max (Imperial)

Mounting Hole Diameter D Max (Metric)

Disc Diameter (Metric) 22.0 Disc Diameter (Imperial) 0.87 Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Material Shortcut PA66HIRHS Flammability **UL 94 HB** UV Resistant (Yes/No) No **Operating Temperature** -40°F to +221°F (-40°C to +105°C) Reach Compliant (Article 33) Yes **ROHS Compliant** Yes Package Quantity (Imperial) 500 Package Quantity (Metric) 500 **Customs Number** 3926909988