

## Specification Sheet

Part Number: 151-00775



HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications. Highly engineered designs feature anti-rattle discs, anti-rotation oval features and clamps for mounting on edges.

An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Conn. Clip w/Arrowhead, 1.7-2.3 mm Panel Thick., 6.3-6.7 mm Hole Dia., PA66HIRHS, Black, 5000/box

|                |           |
|----------------|-----------|
| Article Number | 151-00775 |
|----------------|-----------|

|      |          |
|------|----------|
| Type | CCSFT6.5 |
|------|----------|

|       |            |
|-------|------------|
| Color | Black (BK) |
|-------|------------|

|              |     |
|--------------|-----|
| Quantity Per | bag |
|--------------|-----|

|                     |                                                                                                                                                                                                                                                                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | HellermannTyton connector clips for oval holes are mounted simply by pushing them onto the corresponding clip. The clips provide a wide range of mounting options with anti-rattle and anti-rotation features. The arrowhead locks firmly into place when inserted into the hole palpably and ensures a secure attachment at all times. |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                                   |
|-------------------|---------------------------------------------------------------------------------------------------|
| Short Description | Conn. Clip w/Arrowhead, 1.7-2.3 mm Panel Thick., 6.3-6.7 mm Hole Dia., PA66HIRHS, Black, 5000/box |
|-------------------|---------------------------------------------------------------------------------------------------|

|                  |                       |
|------------------|-----------------------|
| Global Part Name | CCSFT6.5-PA66HIRHS-BK |
|------------------|-----------------------|

|                     |     |
|---------------------|-----|
| Length L (Imperial) | 0.9 |
|---------------------|-----|

|                   |      |
|-------------------|------|
| Length L (Metric) | 23.0 |
|-------------------|------|

|                 |                         |
|-----------------|-------------------------|
| Fixation Method | Arrowhead (Small Mount) |
|-----------------|-------------------------|

|                  |      |
|------------------|------|
| Width W (Metric) | 16.1 |
|------------------|------|

|                     |      |
|---------------------|------|
| Height H (Imperial) | 0.48 |
|---------------------|------|

|                   |      |
|-------------------|------|
| Height H (Metric) | 12.1 |
|-------------------|------|

|                                |      |
|--------------------------------|------|
| Panel Thickness Min (Imperial) | 0.07 |
|--------------------------------|------|

|                                |      |
|--------------------------------|------|
| Panel Thickness Max (Imperial) | 0.09 |
|--------------------------------|------|

|                              |     |
|------------------------------|-----|
| Panel Thickness Min (Metric) | 1.7 |
|------------------------------|-----|

|                              |     |
|------------------------------|-----|
| Panel Thickness Max (Metric) | 2.3 |
|------------------------------|-----|

|                                     |             |
|-------------------------------------|-------------|
| Mounting Hole Diameter D (Imperial) | 0.25 - 0.26 |
|-------------------------------------|-------------|

|                                   |              |
|-----------------------------------|--------------|
| Mounting Hole Diameter D (Metric) | 6.3 - 6.7 mm |
|-----------------------------------|--------------|

|                                         |      |
|-----------------------------------------|------|
| Mounting Hole Diameter D Min (Imperial) | 0.25 |
|-----------------------------------------|------|

|                                         |      |
|-----------------------------------------|------|
| Mounting Hole Diameter D Max (Imperial) | 0.26 |
|-----------------------------------------|------|

|                                       |     |
|---------------------------------------|-----|
| Mounting Hole Diameter D Max (Metric) | 6.7 |
|---------------------------------------|-----|

|                              |                                                                  |
|------------------------------|------------------------------------------------------------------|
| Disc Diameter (Metric)       | 16.0                                                             |
| Disc Diameter (Imperial)     | 0.63                                                             |
| Material                     | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut            | PA66HIRHS                                                        |
| Flammability                 | UL 94 HB                                                         |
| UV Resistant (Yes/No)        | No                                                               |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)                                |
| Reach Compliant (Article 33) | Yes                                                              |
| ROHS Compliant               | Yes                                                              |
| Package Quantity (Imperial)  | 5000                                                             |
| Package Quantity (Metric)    | 5000                                                             |
| Customs Number               | 3926909988                                                       |

