

## Specification Sheet

Part Number: 151-01153



Clip can be installed by hand – no need for hardware or tools.  
Design provides low insertion and high extraction force, for simple, secure performance.

Clip keeps bundle away from areas that could cause damage due to rubbing.

|                |           |
|----------------|-----------|
| Article Number | 151-01153 |
|----------------|-----------|

|      |         |
|------|---------|
| Type | SOC9FT6 |
|------|---------|

|       |              |
|-------|--------------|
| Color | Natural (NA) |
|-------|--------------|

|              |        |
|--------------|--------|
| Quantity Per | carton |
|--------------|--------|

|                     |                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | Standoff bundling clips provide a straightforward way to secure cable bundles, hoses or pipes. The bundle fastens to the tape bar using tape or cable ties. Multiple orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standoff keeps bundles away from mounting area to prevent them from damage due to rubbing. |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                              |
|-------------------|----------------------------------------------------------------------------------------------|
| Short Description | Standoff Bundling Clip, 1.4" Long, Panel Thickness .02 - 0.24", PA66HIRHS, Natural, 4000/box |
|-------------------|----------------------------------------------------------------------------------------------|

|                  |                      |
|------------------|----------------------|
| Global Part Name | SOC9FT6-PA66HIRHS-NA |
|------------------|----------------------|

|                     |     |
|---------------------|-----|
| Length L (Imperial) | 1.4 |
|---------------------|-----|

|                   |      |
|-------------------|------|
| Length L (Metric) | 35.5 |
|-------------------|------|

|                          |     |
|--------------------------|-----|
| Offset Length (Imperial) | 0.8 |
|--------------------------|-----|

|                        |      |
|------------------------|------|
| Offset Length (Metric) | 20.3 |
|------------------------|------|

|                 |          |
|-----------------|----------|
| Fixation Method | Fir Tree |
|-----------------|----------|

|                    |     |
|--------------------|-----|
| Width W (Imperial) | 1.1 |
|--------------------|-----|

|                  |       |
|------------------|-------|
| Width W (Metric) | 27.95 |
|------------------|-------|

|                     |      |
|---------------------|------|
| Height H (Imperial) | 0.47 |
|---------------------|------|

|                   |       |
|-------------------|-------|
| Height H (Metric) | 11.94 |
|-------------------|-------|

|                                |      |
|--------------------------------|------|
| Panel Thickness Min (Imperial) | 0.02 |
|--------------------------------|------|

|                                |      |
|--------------------------------|------|
| Panel Thickness Max (Imperial) | 0.24 |
|--------------------------------|------|

|                              |      |
|------------------------------|------|
| Panel Thickness Min (Metric) | 0.51 |
|------------------------------|------|

|                              |     |
|------------------------------|-----|
| Panel Thickness Max (Metric) | 6.1 |
|------------------------------|-----|

|                                     |             |
|-------------------------------------|-------------|
| Mounting Hole Diameter D (Imperial) | 0.24 - 0.27 |
|-------------------------------------|-------------|

|                                   |              |
|-----------------------------------|--------------|
| Mounting Hole Diameter D (Metric) | 6.1 - 6.9 mm |
|-----------------------------------|--------------|

|                                         |                                                                  |
|-----------------------------------------|------------------------------------------------------------------|
| Mounting Hole Diameter D Min (Imperial) | 0.24                                                             |
| Mounting Hole Diameter D Max (Imperial) | 0.27                                                             |
| Mounting Hole Diameter D Max (Metric)   | 6.9                                                              |
| Material                                | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut                       | PA66HIRHS                                                        |
| Flammability                            | UL 94 HB                                                         |
| UV Resistant (Yes/No)                   | No                                                               |
| Operating Temperature                   | -40°F to +230°F (-40°C to +110°C)                                |
| Reach Compliant (Article 33)            | Yes                                                              |
| ROHS Compliant                          | Yes                                                              |
| Package Quantity (Imperial)             | 4000                                                             |
| Package Quantity (Metric)               | 4000                                                             |
| Customs Number                          | 3926909988                                                       |

