

## Specification Sheet

Part Number: 151-02027

One-piece ratchet closure allows for easy installation during pre- or final assembly.

Easy release feature simplifies quick adjustments and maintenance.

Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.

Stainless-steel mounting plate tolerates high torque and provides superior corrosion resistance against chemicals, salt spray and contact with dissimilar metals.

Angled mounting plates are ideal for stacking RPCs or for avoiding obstructions or heat sources.



Ratchet P-Clamp, 1.38 - 2.01" Bundle Dia, 30° Short, 0.51" Hole Dia, PA66HIRHSUV/SS304, Black, 160/ctn

Article Number 151-02027

Type RCD30SM12SS

Color Black (BK)

Quantity Per carton

**Product Description**

The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws.

**Short Description**

Ratchet P-Clamp, 1.38 - 2.01" Bundle Dia, 30° Short, 0.51" Hole Dia, PA66HIRHSUV/SS304, Black, 160/ctn

**Global Part Name**

RCD30SM12SS-PA66HIRHSUV/SS304-BK

Minimum Tensile Strength (Imperial) 100.0

Minimum Tensile Strength (Metric) 445.0

Length L (Imperial) 7.04

Length L (Metric) 178.8

Fixation Method Screw Mounting

Variant Short

Width W (Imperial) 1.37

Width W (Metric) 34.9

Bundle Diameter Min (Imperial) 1.42

Bundle Diameter Min (Metric) 36.0

|                                       |  |
|---------------------------------------|--|
| Bundle Diameter Max (Imperial)        | 2.0  |
| Bundle Diameter Max (Metric)          | 51.0   |
| Cable Tie Width Max (Imperial)        | 0.52   |
| Cable Tie Width Max (Metric)          | 13.2   |
| Mounting Hole Diameter D (Imperial)   | 0.510  |
| Mounting Hole Diameter D (Metric)     | 12.95 mm   |
| Mounting Hole Diameter D Max (Metric) | 12.95  |
| Stud Diameter (Metric)                | M12  |
| Mounting Hole Centers (Imperial)      | 2.2  |
| Material                              | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Stainless Steel (SS304) |
| Material Shortcut                     | PA66HIRHSUV SS304  |
| Flammability                          | UL 94 HB   |
| Halogen Free                          | Yes  |
| UV Resistant (Yes/No)                 | Yes  |
| Operating Temperature                 | -40°F to +221°F (-40°C to +105°C)  |

Reach Compliant (Article 33) No

ROHS Compliant Yes

UL Listed (US and Canada) Yes

UL Listed (US) Yes

Package Quantity (Imperial) 160

Package Quantity (Metric) 160

Customs Number 3926909988

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)