

Specification Sheet

Part Number: 151-02076

HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. Detailed designs include anti-rattle disc features, anti-rotation oval features, and clamps for mounting on edges.

HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.



Conn. Clip w/Arrowhead, 0.7-3.0mm Panel Thick., 6.5 x 13.0mm Hole Dia., PA66HIRHSUV, Black, 10,000/box

Article Number	151-02076
----------------	-----------

Type	CCIVSFT6.5x130
------	----------------

Color	Black (BK)
-------	------------

Quantity Per	bag
--------------	-----

Product Description	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
---------------------	---

Short Description	Conn. Clip w/Arrowhead, 0.7-3.0mm Panel Thick., 6.5 x 13.0mm Hole Dia., PA66HIRHSUV, Black, 10,000/box
Global Part Name	CCIVSFT6.5x130-PA66HIRHSUV-BK
Length L (Imperial)	0.91
Length L (Metric)	23.0
Fixation Method	Arrowhead (Small Mount)
Width W (Imperial)	0.77
Width W (Metric)	19.6
Height H (Imperial)	0.57
Height H (Metric)	41.6
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.12
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	3.0
Mounting Hole Diameter D (Imperial)	0.26 " x 0.52
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm

Mounting Hole Diameter D Min (Imperial) 0.26

Mounting Hole Diameter D Max (Imperial) 0.52

Mounting Hole Diameter D Max (Metric) 13.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

UV Resistant (Yes/No) Yes

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 10000

Package Quantity (Metric) 10000

Customs Number 3926909988

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)