

Specification Sheet

Part Number: 151-02459



Connector clip design to meet USCAR EWCAP-005-11 clip slot specifications.
Meets installation and extraction requirements of SAE/USCAR-2.
Versatile and robust fir tree design provides low insertion effort yet delivers exceptional retention strength in a 5mm hole and M6 threaded hole.

USCAR Conn. Clip with Fir Tree, 11mm, 5.0 mm Dia and M6 Threaded Hole, PA66HIRHSUV, Black, 5000/ctn

Article Number	151-02459
Type	CC11FTM6
Color	Black (BK)
Quantity Per	carton
Product Description	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
Short Description	USCAR Conn. Clip with Fir Tree, 11mm, 5.0 mm Dia and M6 Threaded Hole, PA66HIRHSUV, Black, 5000/ctn

Global Part Name	CC11FTM6-PA66HIRHSUV-BK
------------------	-------------------------

Length L (Imperial)	0.98
---------------------	------

Length L (Metric)	24.9
-------------------	------

Fixation Method	Fir Tree
-----------------	----------

Variant	M6 Threaded Hole
---------	------------------

Width W (Imperial)	0.622
--------------------	-------

Width W (Metric)	15.8
------------------	------

Height H (Imperial)	0.814
---------------------	-------

Height H (Metric)	20.7
-------------------	------

Panel Thickness Min (Imperial)	0.05
--------------------------------	------

Panel Thickness Max (Imperial)	0.18
--------------------------------	------

Panel Thickness Min (Metric)	1.3
------------------------------	-----

Panel Thickness Max (Metric)	4.5
------------------------------	-----

Mounting Hole Diameter D (Imperial)	0.2362
-------------------------------------	--------

Mounting Hole Diameter D (Metric)	M6
-----------------------------------	----

Mounting Hole Diameter D Min (Imperial)	0.256
---	-------

Mounting Hole Diameter D Max (Imperial) 0.276

Disc Diameter (Metric) 17.5

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

UV Resistant (Yes/No) Yes

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 5008

Package Quantity (Metric) 5000

Customs Number 3926909988

