Specification Sheet

Part Number: 151-03101

Separates bundles to help prevent chafing and wear.
Single bundles can be mounted on top of the mount, or two bundles can be separated using the two side saddles; giving the mount versatility.

Low fire hazard materials comply with stringent NFPA 130 safety standards and improve opportunities to get product specified at the engineering stage of a project.

Low Profile Screw Mount, 1.8" x 0.98", 0.25" Hole, PA666V0, Black, 500/pkg

Article Number	151-03101
Type	LPM25
Color	Black (BK)
Quantity Per	carton
Product Description	Low-profile mounts secure bundles close to mounting surfaces, making them ideal for applications where bundle mounting space is limited. These are secured to the mounting surface with a 0.25" mechanical fastener and feature a counter bore for easy access with a socket. The mount accommodates cable ties up to 0.5" in width. Low fire hazard material is designed specifically for rail applications.
Short Description	Low Profile Screw Mount, 1.8" x 0.98", 0.25" Hole, PA666V0, Black, 500/pkg

Global Part Name	LPM25-PA666V0-BK
Length L (Imperial)	1.8
Length L (Metric)	45.1
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.98
Width W (Metric)	24.9
Cable Ties	T50 - T250
Height H (Imperial)	0.66
Height H (Metric)	16.7
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.7 mm
Mounting Hole Diameter D Max (Metric)	6.7
Material	Polyamide 6.6/6, V0 (PA666V0)
Material Shortcut	PA666V0

Flammability	UL 94 V-0 Low smoke generation Limited fire hazard Halogen-free Low generation of toxic gases and corrosive acid
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Certification/Specification	ASTM 1354 Exova | NFPA130: 2017 ASTM E 162 ASTM E 662
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

© 2023 HellermannTyton. All Rights Reserved.