

Specification Sheet

Part Number: 156-00155



Design provides quick and easy installation by hand without the need for tools
Multiple bundle diameters available for all different ranges of bundles
Clip allows 360 degrees of rotation to attach in any orientation

1-Pc Cable Ties with Pipe Clip, Diameter .26"-.31", 6.0" Long, PA66HS/PA66HIRHS, Black, 500/pkg

Article Number	156-00155
Type	T50SVC6.5
Color	Black (BK)
Quantity Per	bag
Product Description	HellermannTyton's simple to use self-affixing tie allows the attaching of wires or hoses to an existing harness. This allows 360 degree rotation, and the ability to be oriented in any direction in relation to the main harness. This is ideally suited for any application in which the wire or hose can move in relation to the fixing point.
Short Description	1-Pc Cable Ties with Pipe Clip, Diameter .26"-.31", 6.0" Long, PA66HS/PA66HIRHS, Black, 500/pkg

Global Part Name	T50SVC6.5-PA66HS/PA66HIRHS-BK
------------------	-------------------------------

Minimum Tensile Strength (Imperial)	50.0
-------------------------------------	------

Minimum Tensile Strength (Metric)	222
-----------------------------------	-----

Length L (Imperial)	6.1
---------------------	-----

Length L (Metric)	155.0
-------------------	-------

Fixation Method	Omega Clips
-----------------	-------------

Identification Plate Position	none
-------------------------------	------

Width W (Imperial)	0.19
--------------------	------

Width W (Metric)	4.7
------------------	-----

Bundle Diameter Min (Imperial)	0.08
--------------------------------	------

Bundle Diameter Min (Metric)	2.0
------------------------------	-----

Bundle Diameter Max (Imperial)	1.4
--------------------------------	-----

Bundle Diameter Max (Metric)	35.0
------------------------------	------

Mounting Hole Diameter D (Imperial)	0.26 - 0.31
-------------------------------------	-------------

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988