

Specification Sheet

Part Number: 156-00557



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.  
Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

2-Piece Cable Tie & Edge Clip, 8.0" Long, EC24, 3-6 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 500/pkg

|                     |                                                                                                                                                                                                                                                                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 156-00557                                                                                                                                                                                                                                                                                                                                  |
| Type                | T50REC24                                                                                                                                                                                                                                                                                                                                   |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                 |
| Quantity Per        | bag                                                                                                                                                                                                                                                                                                                                        |
| Product Description | HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place. |
| Short Description   | 2-Piece Cable Tie & Edge Clip, 8.0" Long, EC24, 3-6 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 500/pkg                                                                                                                                                                                                                                     |

|                                     |                                        |
|-------------------------------------|----------------------------------------|
| Global Part Name                    | T50REC24-PA66UV/PA66HIRHS-BK           |
| Minimum Tensile Strength (Imperial) | 50.0                                   |
| Minimum Tensile Strength (Metric)   | 225                                    |
| Length L (Imperial)                 | 8.0                                    |
| Length L (Metric)                   | 202.0                                  |
| Fixation Method                     | EdgeClip, sideways, assembled, 2 piece |
| Identification Plate Position       | none                                   |
| Variant                             | Inside Serrated                        |
| Width W (Imperial)                  | 0.18                                   |
| Width W (Metric)                    | 4.6                                    |
| Bundle Diameter Min (Imperial)      | 0.20                                   |
| Bundle Diameter Min (Metric)        | 5.0                                    |
| Bundle Diameter Max (Imperial)      | 2.0                                    |
| Bundle Diameter Max (Metric)        | 50.0                                   |
| Thickness T (Imperial)              | 0.05                                   |
| Thickness T (Metric)                | 1.2                                    |

|                                |                                                                                                       |
|--------------------------------|-------------------------------------------------------------------------------------------------------|
| Height H (Imperial)            | 0.05                                                                                                  |
| Height H (Metric)              | 1.2                                                                                                   |
| Panel Thickness Min (Imperial) | 0.12                                                                                                  |
| Panel Thickness Max (Imperial) | 0.24                                                                                                  |
| Panel Thickness Min (Metric)   | 3.0                                                                                                   |
| Panel Thickness Max (Metric)   | 6.0                                                                                                   |
| Material                       | Polyamide 6.6 UV-stabilized (PA66UV) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut              | PA66UV PA66HIRHS                                                                                      |
| Material Cable Tie             | Polyamide 6.6 UV-stabilized (PA66UV)                                                                  |
| Flammability                   | UL 94 HB                                                                                              |
| UV Resistant (Yes/No)          | Yes                                                                                                   |
| Operating Temperature          | -40°F to +230°F (-40°C to +110°C) -40°F to +185°F (-40°C to +85°C)                                    |
| Reach Compliant (Article 33)   | No                                                                                                    |
| ROHS Compliant                 | Yes                                                                                                   |

|                             |            |
|-----------------------------|------------|
| Package Quantity (Imperial) | 500        |
| Package Quantity (Metric)   | 500        |
| Customs Number              | 3926909988 |